

LİMAKPORT DANGEROUS CARGO HANDLING GUIDE



PREPARATION DATE: 02.06.2022 (Refer to the Revised Revised Page)

> NAME SURNAME SIGNATURE SEAL

REVISION PAGE

Ser.	Revision		Revision	Revision Author			
Nu	Nu	Revision Contents	Date	Name Surname	Signature		
1	0	New Document	02.06.2022	Ceren COLAK			
2	1	Content Update	24.01.2024	Ceren COLAK			
3	2	Facility Information Form Rev (14th art.)	04.11.2024	Ceren COLAK			
4	3	Facility Information Form Rev (16th art.) Removal of the solid load procedure	16.05.2025	Ceren COLAK			
5	3	Fire Plan and Site Plan Update	16.05.2025	Ceren COLAK			
6	3	Chapter 8.4 update	16.05.2025	Ceren COLAK			

CONTENTS

1	ENT	RY	1
	1.1	General information of the port facility	2
	1.2	Loading/unloading, handling and storage procedures for dangerous	
	cargoe	s handled and temporarily stored at the port facility	6
	1.2.1	General	6
	1.3	Procedure for Safe Handling Operation of Packed Dangerous Cargoes	7
	1.3.1	Container	7
	1.3.2	Dangerous cargoes in packaged form	8
	1.3.3	Requirements	8
	1.3.4	Supervision	. 10
	1.3.5	Information for operational and emergency purposes	. 10
	1.3.6	General handling precautions	. 11
	1.4	Safe handling operation of explosives	13
	1.4.1	General	. 13
	1.4.2	Explosives in compatibility group L	13
	1.4.3	Transport of explosives in bad condition	
	1.4.4	Loading and unloading explosives	
	1.4.5	Weather conditions	14
	1.4.6	Additional measures	.15
	1.4.7	Radio or radar transmitting	15
	1.4.8	Bunkering	15
	1.4.9	Damaged nackages	15
	1.4.1	0 Completion of loading	15
	1.4.1	1 Security	16
~			
2	RES	PONSIBILITIES	.17
	2.1	Responsibilities of the relevant person of the goods	17
	2.2	Responsibilities of the port facility operator	17
	2.3	Responsibilities of the ship's master	18
	2.4	Responsibilities of the Carrier	19
	2.5	Responsibilities of the Dangerous Goods Safety Consultant	19
3	POL	ICIES/APPLIED RULES AND MEASURES TO BE FOLLOWED BY PO	RТ
Ē.	ACILITY	/ /	22
• •	31	Rerthing	22
	32	Sunervision	22
	3.2	Identification nacking marking labelling or placarding and	
	cortific	rachine and packing, marking, labering or placar and and	22
	34	Safe handling and segregation	22
	3.5	Fmergency procedures	22
	3.5	Emergency procedures managements and the second s	23
	3.0	Fire procentions	24
	3.8	Fire fighting	24
	3.0	Fire fighting	
	3.10	Dollution combating	25
	3.10	Ponorting of incidents	25
	3.17	Nepot ung of incluents Insportions	
	3.12	Hot work and other renair or maintenance work	
	3.13	Contaminated wastes	
	J.14 3 15	Alcohol and drug abuse	4/ 27
	J.15 2 16	Aiconor anu ui ug abust	
	3.10	11 allillig	

4	CLASSIFICATION OF DANGEROUS GOODS, HANDLING, LOADING /	
U	NLOADING, HANDLING, SEPARATION, STACKING AND STORING	. 28
	4.1 Classification of Dangerous Goods	28
	4.2 Dangerous Goods Packing and Packages	30
	4.3 Dangerous Goods Marking, Labels, Placards	32
	4.3.1 Labels	32
	4.3.2 Placards	32
	4.4 Packaging and Approval Marking.	37
	4.4.1 Packing Groups, Classifying Criteria	37
	4.4.2 UN Packaging and Approval Marking	37
	4.5 Segregation and Separation	38
	4.5.1 Principles of segregation and stowage	38
	4.5.2 IMDG Code segregation, stowage and Dangerous Goods list	39
	4.6 Separation distances and separation terms for hazardous materials	
	applicable storage at storage area	41
	4.6.1 Segregation Categories	41
	"Separated from"	41
	4.6.2 Segregation within the Cargo Transport Units	42
	4.6.3 Segregation in Port Areas	42
5	HANDBOOK OF DANGEROUS GOODS	.44
~	DDOCEDUDEC FOD THE ODED ATION	4 5
0	PROLEDURES FOR THE OPERATION	.45
	6.1 Prosedure of snips carrying dangerous goods safely Bertning, loading	;/
	unioading, sheller of anchorage during the day and at hight	45
	0.2 Procedure of according to the seasonal conditions additional measure that Loading /Unloading limbo operation of dangerous goods should be take	25
	that Loading/ onloading, minor operation of dangerous goods should be take	н 16
	6.3 Procedures on keeping any inflammable combustible and evalosive	40
	materials away from operations which cause or are likely to cause sparking	and
	abstaining from operating any tools, annaratus or device which cause or are	ana
	likely to cause sparking in areas where hazardous materials are handled.	
	stowed and stored	47
_		
7	Documentation, Control And Record	.48
	7.1 Procedures regarding to all necessary documents, information and	
	certification relating to dangerous substances and their procurement and	40
	control by the relevant persons	48
	7.2 Procedures of keeping a regular and accurate current list of all	
	nazardous substances in the coastal facility area and other relevant	40
	11101111dulloll.	40
	7.5 Procedures regarding to appropriate identification of nazardous substances delivered to the facility, correct use of shipping names of danger	
	substances derivered to the facility, correct use of simpping names of danger)us
	and transport of dangerous goods in the certified and proper package	Ig
	container or cargo unit in a safety way and renorting of inspection results	50
	7.4 Procedures related to procurement of the Hazardous materials safety	7
	information sheets (SDS)	
	7.5 Procedures for records and statistics of dangerous goods	
	7.6 Information on the Quality Management System	
~		
8	EMERGENCY SITUATION, EMERGENCY PREPAREDNESS AND RESPON	SE

8.1 Response procedures for hazardous substances that are dangerous life, property and/or environment and hazardous situations involving	for
8.2 Information on resource canability and canacity of the coastal facil	lities
regarding to respond to emergencies.	
8.3 Regulations related to the first aid for accidents involving dange	erous
substances (first aid procedures, first aid resources and capabilities and se	o on.).
57	-
8.4 On-site and off site Notifications required to be made in case of	
emergency	58
8.5 The procedures for reporting accidents	58
8.5.1 Communication	59
8.5.2 Reports	59
8.6 Coordination, support and cooperation method with authorities	59
8.7 Emergency evacuation plan for the evacuation of the ship and vesse	els
from the coastal facility in case of emergency	61
8.7.1 Preparation for Emergency Seperation System	
8.7.2 Realization of Emergency Separation	
8.7.5 Post Emergency Separation	62
8.8 Procedures for handling and disposal of the damaged hazardous go	oas
and wastes contaminated with hazardous goods.	03
8.8.1 Waste coneculig and nanoning	03
0.0.2 Waste uisposal	03
8.0.5 Containinateur rackages,	03 64
8.9 1 Implementation of Practices:	04 64
8.9.7 Practice Scenarios	04 64
893 Fmergency Practices which will be performed within the facility	- 64
8 10 Information on fire protection systems	01 64
8.11 Procedures for approval, inspection, testing, maintenance and	
availability of the fire protection system	65
8.11.1 Fire-Protection Water Tanks and Fire-Protection Water	65
8.11.2 Fire-Protection Water Pumps	65
8.11.3 Sprinkler System	66
8.11.4 Fire Protection Hydrant Installation	66
8.11.5 Portable Extinguishers	67
8.11.6 Protection against freezing	67
8.12 The measures to be taken in case of failure on fire protection system	ms. 68
8.13 Other risk control equipment	68
Ο ΓΛΕΕΤΎ ΑΝΌ Η ΕΛΙ ΤΗ ΑΤ ΜΟΟΚ ΜΕΛΟΙΟΕς	69
 SAFETTAND HEALTHAT WORK MEASURES 0.1 Occupational health and safety measures 	60
0.1.1 Dick accosmont	
9.1.1 RISK dssessifient	00
9.1.2 Emergencies 9.1.3 Workers' aducation and informing them	70 71
9.1.5 Workers cutcation and morning them	/ 1 to uso
them 71	to use
9.3 Closed Room Entry Permit Precautions and Procedures	72
10 OTHER POINT	74
10.1 Validity of the Hazardous Substances Compliance Certificate	
10.2 Responsibilities of the Dangerous Goods Safety Consultant	74
10.3 Matters for carriers of the hazardous substances arriving/leaving	
coastal facility by land (matters on required documents that must be avail	able
in the road vehicle at the entrance/exit of port or coastal facility area,	

equipment and tools required for this vehicles, speed limits in the port area	
10.3.1 Packaged dangerous cargoes and bulk dangerous cargoes (liqui	d or
solid): 75	
10.3.2 Necessary certificates	75
10.3.3 Speed Limit in Port Facility	75
10.4 Matters for carriers of the hazardous substances arriving/leaving	
coastal facility by sea (matters on day/night signals to be shown by ships	
carrying hazardous goods and vessels, cold and hot work procedures in ship)S
and so on.)	76
10.4.1 Arrival by Sea	76
10.4.2 Departure by Sea	77
10.5 Additional points will be added by the port facility	78
10.5.1 Training	78
10.5.2 Training content	78
11 ANNEXES	79
11.1 General Lavout Plan of the Coastal Facility	
11.2 General Appearance Photographs of the Coastal Facility	80
11.3 Emergency Contact Points and Contact Information	81
11.4 General Layout Plan of Areas Where Dangerous Cargoes Are Handled	182
11.5 Fire Plan of Areas Where Dangerous Cargoes Are Handled	83
11.6 General Fire Plan of the Facility	84
11.7 Emergency Plan	85
11.8 Emergency Assembly Places Plan	85
11.9 Emergency Management Scheme	86
11.10 Hazardous Materials Handbook	87
11.11 11.11 Leakage Areas and Equipment, Entry/Exit Drawings for CTU	and
Packages 87	
11.12 Inventory of Port Service Vessels	88
11.13 Sea coordinates of Port Authority administrative borders, anchora	ige
areas and pilot disembarkation/embarkation points	89
11.14 Emergency Response Equipment Against Marine Pollution in the P	ort
Facility 90	
11.15 Personal protective equipment (PPE) usage map	90
11.16 Hazardous Material Incident Notification Form	91
11.17 Control Results Notification Form for Hazardous Cargo Transport	00
Units (CTUS)	92
12 ABBREVIATIONS	93
13 PRESENTATION	93
14 DEFINITIONS	94

l imakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	1		
	DANGEROUS CARGO HANDLING GUIDE						

1 ENTRY

1.1. The entry and presence of dangerous cargoes in port areas and any consequential handling should be controlled to ensure the general safety and security of the area, the containment of the cargoes, the safety of all persons in or near the port area, and the protection of the environment.

1.2. The safety of life at sea and the safety and security of a ship, its cargo and its crew in a port area are directly related to the care which is taken with dangerous cargoes prior to loading or unloading, and during their handling.

1.3. These Recommendations are confined to dangerous cargoes which are in a port area as part of the transport chain. These Recommendations do not apply to dangerous substances which are used in a port area or are for general storage in the port area, but Governments may wish to control such use and storage by national legal requirements. Should a substance covered by either of these exclusions subsequently be shipped, these Recommendations should then be applied, even though the substance is already in the port area.

1.4. An essential pre-requisite for the safe transport and handling of dangerous cargoes is their proper identification, containment, packaging, packing, securing, marking, labelling, placarding and documentation. This applies whether the operation takes place in a port area or at premises away from a port area.

1.5. Whilst the total transport chain includes inland, port and marine elements, it is essential that every care is taken by those responsible for the matters in 1.4 and that all relevant information is passed to those involved in the transport chain and to the final consignee. Attention should be paid to the possible differing requirements for different modes of transport.

1.6. The safe transport and handling of dangerous cargoes is based on correct and accurate application of regulations for transport and handling of such cargoes and depends on appreciation by all persons concerned of the risks involved and on the full and detailed understanding of the regulations. This can only be achieved by properly planned and carried out training and retraining of persons concerned.

1.7. The codes and guides are under continuous review and are regularly revised. It is essential that only the most up-to-date editions are used. The contents of these codes and guides have been repeated in these Recommendations only to the extent necessary.

1.8. In preparing this guide IMDG CODE, ERG 2016 and IMO 1216 CR. documents have been applied to and the informations are used.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No			
iskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	2			
	DANGEROUS CARGO HANDLING GUIDE							

1.1 General information of the port facility

General information about the facility is as in the facility information form presented below.

1	Facility operator name/title	LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT INC.				
2	Contact information of the facility operator (address, telephone, fax, e-mail and web page)	LIMAK İSKENDERUN INTERNATİONAL PORT MANAGEMENT INC. : 5 July Cad. End in Iskenderun/HATAY Telephone: 03266261600 Fax: 0326 6140048 garisoy@limakports.com www.limakports.com.tr				
3	Facility name	LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT INC.				
4	City where the facility is located	Hatay				
5	Contact information of the facility (address, telephone, fax, e-mail and web page)	LIMAK İSKENDERUN INTERNATİONAL PORT MANAGEMENT INC. : 5 July Cad. End in Iskenderun/HATAY Telephone: 03266261600 Fax: 0326 6140048 garisoy@limakports.com www.limakports.com tr				
6	Geographical region of the facility	Eastern Mediterranean				
7	Port Authority and contact details of the facility	Iskenderun Port Authority Telephone: 03266141192 Fax: 03266140226				
8	Mayor's Office and contact details of the facility	Iskenderun Municipality Tel: 03266134990 Fax: 03266145333				
9	Name of the Free Zone or Organized Industrial Zone where the facility is located	-				
10	Validity date of Coastal Facility Operation Permit/Temporary Operation Permit	18.03.2026				
11	Operating status of the facility (X)	Own cargo and additional 3rd party ()Own load ()3rd Party (x)				
12	Name and surname of the facility manager, contact details (phone, fax, e- mail)	Gündüz ARISOY/ General manager Tel: 03266261600 Fax: 0326 6140048 garisoy@limakports.com				

l imakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
İskenderun	RH-TMG-001	02.06.2022	3	3 16.05.2025			
	DANGEROUS CARGO HANDLING GUIDE						

13	Name and surname, contact details (phone, fax, e-mail) of the dangerous goods operations officer of the facility	Temel SEZER Tel: 03266261600 Fax: 0326 6140048 tsezer@limakports.com
14	Name and surname of the Dangerous Goods Safety Advisor of the facility, contact details (phone, fax, e-mail)	Seren KARAASLAN E-Posta: seren@tmgddanismanlik.com Telefon: 0534 892 7582
15	Marine coordinates of the facility	latitude 36° 35' 50" N / longitude 36° 11' 20" E
16	Types of dangerous goods handled at the facility (Loads within the scope of MARPOL Annex-I, IMDG Code, IBC Code, IGC Code, IMSBC Code, Grain Code, TDC Code, asphalt/bitumen and scrap loads)	IMDG Code ((except Class 6.2 and Class 7),Grain Kod
17	Dangerous goods handled at the facility (loads other than IMDG Code, among the cargo types in Article 16, will be written separately. Additional cargo request will be sent to the port authority with Annex-1 form. It will be added to TYER when appropriate)	N/A
18	Classes for cargo handled, subject to IMDG Code	IMDG Code ((except Class 6.2 and Class 7)
19	Groups in characteristic table for handled cargo subject to IMSBC Code	-
20	Types of ships that can approach the facility	Container, Bulk Cargo, General Cargo, Ro-Ro, Livestock
21	Distance of the facility to the main road (kilometers)	0,2 km
22	The distance of the facility to the railway (kilometers) or the railway connection (Yes/No)	Yes
23	Name of the nearest airport and its distance from the facility (kilometers)	Hatay Airport: 50 km.
24	Load handling capacity of the facility (Ton/Year;TEU/Year;Vehicle/Year)	3.000.000 tons/year, 1.300.000 TEU/year, 100.000 CEU/year
25	Whether scrap handling is done at the facility	No
26	Is there a border gate? (Yes No)	Yes
27	Is there a bonded area? (Yes No)	Yes
28	Cargo handling equipment and capacities	Gantry Container Handling Crane (STS): 4 units Single container 50t Twin-twenty: 65t Under cargo beam: 75t Rubber Wheel Gantry Container Handling Crane (RTG): 13 units - 41 tons

ſ	limakDort	Döküman No	Yayın Tar	ihi	Rev. No	Revizyor Tarihi	1	Sayfa No	
	LIIIIANF UIL İskenderun	RH-TMG-001	02.06.202	2	3	16.05.2025		4	
		DAN	GEROUS CA	ARGO) HANDLI	NG GUIDE			
				Mo Full Em tons For Sen Sub For For For	bile Harbo l Containe pty Conta s klift: 2 un nebogen 8 ocontracto klift: 3 un klift: 4 un klift: 3 un	or Crane (M or Stacker (C iner Stacker its - 3 tons 370: 1 unit 2 r Handling 1 its 32 tons its 16 tons its 9 tons its 5 tons	IHC) CRS r (EC 22.5 Equi): 2 units - 1): 6 units - 3 CH): 3 piece tons	124 tons 35 tons es - 9
				For	klift: 23 u	nits 3 tons			
				Loa	der 3 unit	s			
			Boł	ocat 1 unit					
2	9 Storage tar	nk capacity (m3)		-					
3	O Open stora	ge area (m2)		763	.127 m2				
31	Semi-close	ed storage area (m2)		-					
3	2 Closed stor	rage area (m2)		17.5	545 m2				
3	3 Determined fumigation	d fumigation and/or d area (m2)	le-	540	m^2				
3.	34LIMAK İSKENDERUN INTERNATİONA PORT MANAGEMENT INC. 5 July Cad. End in Iskenderun/HATAY Telephone: 03266261600 Fax: 0326 6140048				NAL Y				
3	5 Has a Secu No)	rity Plan been created	d? (Yes	YE	S(ISPS co	de)			
					Waste	Гуре		Capacity ((m3)
					ge		159		
				slud	ge		159		
				slud	ge		159		
	Waste Rec	eption Facility capaci	ty	slud	ge		71		
36	(This section	on will be arranged se	eparately	bilge	e		159		
	according t	according to the wastes accepted by the facility)			e		159		
	facility)						71		
				Dew	atered Bilge	2	71		
				was	te oils		/1	0	
				Tota	1		115	U	
37	Dock/pier	etc. properties of field	ds						

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	5	
	DANGEROUS CARGO HANDLING GUIDE					

Dock / Pier No	Height (meter)	Width (meter)	Maximum water depth (metre)	Minimum water depth (metre)	The largest ship tonnage and length to berth (DWT)
Dock no. 1-2	370	33	15,5	14,5	60.000 DWT
Dock no. 3-4	550	33	15,5	15,5	60.000 DWT
Dock no. 5-6	256	48,5	11	7,5	40.000 DWT
Dock no. 7-8	256	48,5	12,5	9	40.000 DWT
Pipeline name (if available on site)			Number (piece)	Length (metre)	Diameter of (inch)
no					

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	6	
	DANGEROUS CARGO HANDLING GUIDE					

1.2 Loading/unloading, handling and storage procedures for dangerous cargoes handled and temporarily stored at the port facility

1.2.1 General

1.2.1.1 Loads defined as class 7 radioactive substances and class 6.2 infectious substances in the IMDG Code are not allowed into the facility. These cargoes are defined as dangerous cargoes which cannot be permitted absolutely and if the regulatory authority permits, they are processed as transit cargo. They are loaded and unloaded at a private area within the port facility and taken away by dispatching without keeping them at the port facility. Necessary Class 1 handling equipment and safety precautions are available regarding the container operation. Cargoes which are wrapped, packed or prepared in the form of bale/bunch/truss within the scope of IMDG codes general cargoes and project cargoes are handled.

1.2.1.2 Fulfillment of the conditions specified below will be ensured as regards handling the dangerous cargoes coming to the port facility, keeping them temporarily at the port facility, making their stowage and segregation and storage for safety of the port facility, employees and ships at the port facility.

1.2.1.2.1 Before the acceptance of hazardous cargoes to the shore facility, detailed information about the product (Cargo SDS, Conchimneto, operation details, etc.) is obtained by customer services and OHS, TMGD, Environment and Operation unit is informed via e-mail. The product is evaluated within the framework of operation risks and authorization, and approval is given to the customer after the operation suitability.

1.2.1.2.2 Translated with DeepL.com (free version)Following issues will be discussed during the coordination meeting with regard to the dangerous cargo (es) to be accepted to the port:

- 1. Risk arising from dangerous cargo
- 2. Interaction with dangerous cargoes existing at the port facility,
- 3. Interaction with cargoes planned to be accepted to the port facility in the near future,
- 4. Conditions for stowage
- 5. Adequacy of storage space
- 6. Environmental risks
- 7. Conditions for segregation
- 8. Requirement of materials and equipment with respect to emergency response
- 9. Sufficiency of emergency response equipments
- 10. Interaction with the neighboring area (s)

The issues are handled within the scope of the current IMDG CODE for packaged loads and an acceptance / rejection or management decision is made.

1.2.1.2.3 If the decision is taken to accept the dangerous cargo in the assessment, management, operation, storage, security, emergency response units are informed and the preparation and acceptance process is started..

1.2.1.2.4 If it is required to notify the Port authority, the situation shall be notified to the Port authority in writing by specifying the reasons.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	7		
	DAN	DANGEROUS CARGO HANDLING GUIDE					

1.3 Procedure for Safe Handling Operation of Packed Dangerous Cargoes

1.3.1 Container

1.3.1.1 The container transporting dangerous materials subject to customs regime has been declared to the Customs Authorities; and the Customs Administration, as per the declaration, orients such container to RED line for physical examination and document control, to YELLOW line for control of correctness without need to physical examination, to BLUE line where the declarations and documents will be controlled later, to GREEN line where documents are not controlled and goods are not physically checked and determines the conduction of COMPLETE DETERMINATION, PARTIAL EXAMINATION or EXTERNAL EXAMINATION.

1.3.1.2 Customer or the representative Agent thereof will make a request at the agency port (registry office, commercial tariff unit, CFS office) and a service order will be formed. Opening and closing minutes shall be signed by the customs examiner and a request will be made to CFS office with these minutes and the declaration.

1.3.1.3 If the dangerous material inside the container does not have material safety data sheet (SDS), it will be requested from the customer or his representative. Proceedings shall not be started for dangerous cargoes which do not have SDS. SDS is reviewed by operation and HSE/TMGD departments and the required measures are taken and assignment of teams is carried out.

1.3.1.4 The container, requested in line with the Service Order issued by CFS office, is brought to CFS site.

1.3.1.5 The container is loaded on the Port Vehicle at the stowage area and brought to the CFS area and unloaded at the planned location. The examination of container is completed under the control of the customs examiner, customer/his representative and port CFS operation authority and the Opening and Closing minutes is prepared.

1.3.1.6 During the Examination and Sampling process, teams wearing Protective Clothing will intervene the wastes (packaging paper, plastics, fixing materials etc) and leakage from the container in which there are Dangerous Materials and will perform the cleaning. The wastes will be taken to the waste collection center to be disposed.

1.3.1.7 The completed Container is taken to the Container stowage area by assigning it to the area. It is taken to the dangerous cargo stowage area, which is predetermined for dangerous cargoes and necessary precautions are taken.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	8	
	DANGEROUS CARGO HANDLING GUIDE					

1.3.1.8 Containers containing Dangerous Goods are not placed in the "Temporary storage place closed warehouse" according to Article 77 of the Customs Legislation and are taken to general or special warehouses suitable for the qualifications of these containers.

1.3.2 Dangerous cargoes in packaged form

1.3.2.1 Packaged dangerous cargoes other than dangerous cargoes coming in containers will be shipped / discharged after storage or as supalan, taking into account the need and facility conditions in our coastal facility.

1.3.2.2 The loading or unloading program will be prepared 1 day before at the operation meeting. Number of equipments and cranes, teams and shifts as well as the port to be used shall be specified at this meeting. The personnel who will work in the operation will be provided with information as regards the risks of the cargo and they will be equipped with the necessary protective outfit. Environmental safety is ensured by the HSE unit. Personnel will be employed neither in the hold of the ship nor in the work area prior to the conduction of gas measurements.

1.3.2.3 Necessary warnings will be made in order that the trucks do not to make loading exceeding loading limit and people in charge will pay necessary attention with respect to this issue.

1.3.2.4 The drivers will wait at a specified location away from the vehicle during the loading and unloading of vehicles. It will be controlled if the driver has the necessary protective equipments or not.

1.3.2.5 The shift superintendent will be responsible from controlling the work security, control of equipments, entry and exit of outsiders, safe handling of the cargo, environmental cleaning and duly performance of these works.

1.3.2.6 Working order will be organized through the berth operator, steersman and chief officer of the ship. Berth operator ensures the realization of loading or unloading as per the cargo plan. The responsibility of loading and unloading as per the cargo plan belongs to the Berth Operator.

1.3.3 Requirements

1.3.3.1 The facility is equipped with water pump with electrical and diesel motor for cooling having connections with water tanks with adequate volume, fire hydrant connected with fire pipes in adequate number/size in required places, fire cupboard, spare energy production devices with adequate power (generators), fire equipments, details of which are provided in Article 8.10 containing fire extinguishing devices consisting of those operating with foam (for fire extinguishing works other than buildings and liquidated gas fires) dry chemical/powder which are fixed/mobile, depending on the capacity of the facility and the location thereof.

It will be ensured that the personnel involved in the loading/unloading of packaged dangerous goods at the coastal facility receive training on emergency situations (fire, explosion, leakage, etc.) and response, occupational health and safety, ISPS code security awareness in accordance with their job descriptions and work areas. ..

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	9	
	DANGEROUS CARGO HANDLING GUIDE					

1.3.3.2 Works and processes related with damaged cargo carrying units and packagings containing dangerous materials shall be carried out by taking necessary measures at CFS's worksite. If there are any leakages in the said cargo carrying units or packagings, works related to them will be performed at the mobile leakage pools with capacity of 40-feet containers.

1.3.3.3 IMO work area has been allocated which is in compliance with segregation and storage rules for packed dangerous cargoes and containers carrying dangerous materials and temporary storage of the said packaged dangerous cargoes will be carried out as per segregation and storage rules stated in section 4. Required fire, environmental and other safety measures will be taken at these worksites. If handling and storage of dangerous materials are done at the entire worksite, then the roads will be open for reaching the units carrying cargo containing dangerous materials and the equipments enabling emergency response for intervening within a short period shall be made available at the worksite.

1.3.3.4 The communication means used will be working, in good condition and adequate number and capacity to provide safe usage and uninterrupted communication in loading or unloading and handling operations of dangerous cargoes

1.3.3.5 It will be controlled to ensure that the required warnings, signs and alarm buttons are placed at a visible and easily reachable location. The related personnel will be equipped with protective clothing and equipment in accordance with the work safety and health criteria at locations and situations which are dangerous. Personnel who don't have protective clothing and adequate equipment in line with their job descriptions and their working areas will not be employed.

1.3.3.6 Cargo transport units transporting temperature-controlled dangerous materials can only be temporarily stored at IMO area where the necessary measures are taken. The temperature values of the cargo transport units will be followed up constantly and also be remotely monitored as much as applicable.

1.3.3.7 Packages containing Class 4.3 dangerous substances which, in contact with water, emit flammable gases and cargo transport units containing these types of packages will be stored at closed areas which are not affected from factors like rain, sea water and etc. Warning signs specifying the risks will be placed at the areas of storage. Cargo Transport Units (CTUs) containing the said dangerous materials could be stored in open facility areas if they are not affected from factors like rain, sea water and etc.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	10	
	DANGEROUS CARGO HANDLING GUIDE					

1.3.4 Supervision

1.3.4.1 After the approach of the ship to interface, the master and port authority will supervise the transport of dangerous cargoes within their respective areas of responsibility while the shift superintendent or the berth operator will ensure performance of proceedings in line with the risks related to the cargo and they shall notify the master regarding steps to be taken in emergency cases.

1.3.4.2 The responsible person for the ship will usually be the chief officer or cargo officer. These persons will ensure the continuity of communication with the shift superintendent or the person responsible with operations.

1.3.5 Information for operational and emergency purposes

1.3.5.1 The persons responsible from operation, within their respective areas of responsibility, should have the following information with respect to all dangerous cargoes transported or handled immediately available:

1.3.5.2 The description of dangerous cargoes in accordance with Chapter 5.4 of the IMDG Code;

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	11		
	DAN	DANGEROUS CARGO HANDLING GUIDE					

1.3.5.3 Details of special equipment needed for the safe handling of a particular dangerous cargo; and

1.3.5.4 The emergency procedures, including action to be taken in the event of a spillage or leakage, counter measures against accidental contact, fire-fighting procedures and suitable fire-fighting media.

1.3.5.5 Information in respect of required special equipment and relevant testing and examination certificates should be immediately available to the master, the berth operator and the responsible persons.

1.3.5.6 Information as to emergency case procedures will be provided to the ship and people responsible from handling of cargo. The information should be placed in a location immediately accessible to the persons concerned, e.g., aboard ship in the cargo office, at the berth in a place which is easily accessible by the responsible people.

1. This information will include emergency procedures at the berth, fire and emergency arrangements at the berth and telephone numbers of the fire brigade, ambulance, police and competent authorities to be notified in the event of an accident involving dangerous cargoes.

2. In the event of an accident involving dangerous cargoes, the port officer's telephone and emergency telephone number to be called will also be included.

1.3.5.7 Berth operator will be responsible of keeping record of positioning of dangerous materials being transported on the ship or in port facility and the berth operator will notify the duties in writing. Berth operator will keep these records about the positioning of dangerous materials and make them available in case of emergency to relevant persons and keep them in an easily accessible way for the relevant persons

1.3.6 General handling precautions

1.3.6.1 Berth operator within its respective areas of responsibility, should ensure that:

1. Every person engaged in the handling of dangerous cargoes exercises reasonable care to avoid damage to packages, unit loads and cargo transport units.

2. Whilst dangerous cargoes are being handled, precautions are taken to prevent unauthorized access to handling areas.

3. If there is any loss of containment of dangerous cargo, every practical step is taken to minimize risks to persons and adverse effects to the environment.

4. Wrappings and packaging to be used in the activities of changing of cargo transport units, repair thereof or placing of the damaged packages inside the saving packages should be in accordance with the structure of dangerous materials and they shall be produced and certified as they are set out in chapter 6 of the IMDG Code

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	12	
	DANGEROUS CARGO HANDLING GUIDE					

5. Provisions of Code of Practice for Packing of Cargo Transport Units (CTU code) will be considered during internal loading process and/or loading process of other transport mode vehicles of the cargo transport units within the port facility. CFS personnel responsible of area shall issue a Container/Vehicle Packing Certificate if loading of a container or vehicle is performed at the areas of the facility where cargo transport units are unloaded and/or at the closed warehouses (CFS areas). It will be checked whether each cargo transport unit coming to the port facility for transportation by the sea has got "Container/vehicle packing certificate" or not at the entry points to the port and it will not be permitted for cargo transport units to make loading to the ship if they don't have the required certificate.

6. The handling and temporary storage operations shall be conducted as per the rules specified on table 1 (Schedule for segregation of the dangerous cargoes at the port facility) within the annex of "Recommendations on the Safe Transport of Dangerous Cargoes and Related Activities in Port Areas" as part of circular with no MSC/Circ.1216 of the International Maritime Organization. Details are provided in Chapter 4.

7. Fumigated cargo transport units and/or cargo transport units containing poisonous gases shall be stowed in a manner that their covers cannot be opened in an uncontrolled way.

8. Cargo transport units by which dangerous materials with temperature control are transported will be temporarily stored at the IMO area after the required precautions are taken. The temperature values of these cargo transport units will be constantly monitored and followed up through the camera system.

9. There is no closed area for packages containing dangerous materials releasing flammable gases when contacted with water and for cargo transport units containing them. If containers including class 4.3 type cargo possess qualities which won't be affected by wind, sea water or similar factors, they can be stowed at the IMO facility by considering the related rules. In other cases, it will not be allowed to handle and let them enter the port facility.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	13	
	DANGEROUS CARGO HANDLING GUIDE					

1.4 Safe handling operation of explosives

1.4.1 General

1.4.1.1 It will be ensured that related instructions are given to control the vehicles used in transport of explosives within port facility.

1.4.1.2 Presence of a person responsible of the explosive cargo at the port facility always will be ensured.

1.4.2 Explosives in compatibility group L

1.4.2.1 Explosives included in compatibility group L will not be taken to the port facility without obtaining the required permissions from the port regulatory authority.

1.4.3 Transport of explosives in bad condition

1.4.3.1 Damaged cargo transport units containing explosive materials will not be taken to the ship and/or to the port facility. Should any damages occur during handling of cargo transport unit or the explosive materials inside, the operation will be ceased immediately and the relevant parties will be notified. Replacement of damaged cargo transport units or packaging containing explosive materials will be conducted under the supervision of explosive experts by taking the related safety and security measures and by obtaining permissions from related institutions at the area specified for temporary storage.

1.4.4 Loading and unloading explosives

1.4.4.1 Handling of explosive materials at the port facility is prohibited if the required permission for handling of explosive materials is not given through the regulatory authority. Accordingly, ships carrying explosive materials as transit cargo to port facility not having permission for handling explosive materials will be allowed only by receiving approval of the relevant regulatory authority on condition that the materials are not unloaded at the port facility.

1.4.4.2 Class 1 type explosive materials other than those within class 1.4 compatibility group S will be handled at the port facility on the condition that they are loaded to the ship without waiting or are taken out of the port facility without waiting unless special permission is obtained from the regulatory authority,.

1.4.4.3 The ship or the vehicle loading of which is completed will leave the port facility as soon as possible after the loading of explosive materials is completed at the port facility.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	14	
	DANGEROUS CARGO HANDLING GUIDE					

1.4.4.4 If storage of explosive materials is needed temporarily at the port facility due to force majeure although the organizations required for handling these materials have been made before, these materials can be temporarily stored for a maximum period of 24 (twenty four) hours at a specified area determined at the port facility by getting permits from the related institution (s) by taking the required safety measures. The details of the temporary storage area are given in Annex-11.4. These points will be surrounded by iron barriers and a security check point will be established. It is continuously monitored with the camera system. Ship operation and freight operations will not be conducted as long as they are on the pier.

1.4.4.5 The port facility where explosive materials are handled will be marked by specifying them as "protected area" and the boundaries of this area will be at least 10 (ten) meters wider than the normal handling area.

1.4.4.6 Smoking and other sources of ignition, carrying and using matches or lighters, presence of any device, equipment or outfit which can create flames or sparks are prohibited at the areas where explosive materials are handled and the responsible personnel shall wear appropriate work uniforms and have protective outfit.

1.4.4.7 Equipment to be used in the handling of explosive materials should be of an approved type according to international standards and their testing and maintenance work should be duly carried out

1.4.4.8 As long as a permission is not obtained from the relevant port authority, the ship which is loaded with explosive materials or loading/unloading of which will be made will be approached to the berth/pier in a way that its port is in direction of going out from the berth to the sea. Steel wire rope will not be used to moor the ship to the berth/pier.

1.4.4.9 There will be a steel wire rope with housing at the end at the prow and stern of the ship near to water level during the time a ship loaded with explosive materials or of which loading or unloading of explosive materials will be made is moored at the port as to enable intervention by towing boats when required.

1.4.4.10 No repair and maintenance work will be done in the machines of a ship loaded with explosive materials without the permission of port authority even though it may be needed for the departure of the ship from the port.

1.4.5 Weather conditions

1.4.5.1 Because of the nature of explosives, the provisions of Chapter 3 with respect to the handling of dangerous cargoes in adverse weather conditions need careful attention, particularly in respect of wet conditions.

1.4.5.2 Measures will be taken to prevent wetting of explosive materials.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	15	
	DANGEROUS CARGO HANDLING GUIDE					

1.4.6 Additional measures

1.4.6.1 No source of ignition should be brought into or near to a place where explosives are being handled. The wearing of shoes or boots with unprotected metal nails, heels or tips of any kind should be prohibited, except where the consignment consists only of articles of class 1, and care taken to ensure that any portable lights and other electrical equipment are of a type safe for use in a flammable atmosphere.

1.4.7 Radio or radar transmitting

1.4.7.1 During the handling of explosives no radar or radio transmitter should be used within 50 metres of the cargo handling area

1.4.7.2 No radar or radio transmitter except for VHF transmitters with power output less than 25 Watts should be used on the ships, cranes or at any place near them during the loading and unloading of explosive materials. Power units of these devices will be closed during the handling of explosive materials and they are marked visually to avoid their being opened during the handling process. Furthermore, VHF transmitters will not be places closer than 2 meters to the explosive materials during usage thereof.

1.4.8 Bunkering

1.4.8.1 No bunkering should be permitted during the handling of explosives or while the hatches of cargo spaces containing explosives are open, unless the permission of the port authority has been obtained

1.4.9 Damaged packages

1.4.9.1 If in the course of handling explosives in the port area any package of explosives, or the seal of any such package, appears to be damaged, that package should be set aside for examination and repair or other safe disposal

1.4.9.2 If any explosives are spilled or escape from a package, the responsible person supervising the handling should ensure that such spillage is immediately collected and safe arrangements are made for its repacking or disposal.

1.4.10 Completion of loading

1.4.10.1 When loading is completed the loaded ship or vehicle should depart from the port area as soon as is reasonably practicable.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	16	
	DAN	DANGEROUS CARGO HANDLING GUIDE				

1.4.11 Security

1.5.11.1 As the safety of the handling of explosives is affected by the degree of safety attained, consideration should be given to all safety measures necessary to prevent unauthorized access to explosives, including appropriate checks that all packages are received in good order and condition at all stages of the handling operation. Explosives should neither be moved nor handled unless the relevant permits have been issued and such tasks should be undertaken in accordance with the conditions specified in the relevant permits.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	17		
	DAN	DANGEROUS CARGO HANDLING GUIDE					

2 RESPONSIBILITIES

All parties involved in dangerous cargo transportation activities are obliged to take all necessary measures to ensure safe, secure and environmentally friendly transportation, prevent accidents and minimize damage as much as possible when there is an accident. The EmS Manual, which contains Emergency Response Methods and Emergency Rulers for Ships Carrying Dangerous Goods in case of emergency situations such as fire, leakage, debris that occur during the transportation of dangerous goods is used.In order to properly provide the necessary medical first aid to people affected by damages of dangerous goods and health problems caused by accidents involving these loads, the "Medical First Aid Guide (MFAG)" contained in the IMDG Code Annex is used.

2.1 Responsibilities of the relevant person of the goods

- **2.1.1** Prepare, has prepared all mandatory documents, information and documents related to dangerous goods and to ensure that these documents are present with the cargo during the transportation activity.
- **2.1.2** Provides for the classification, identification, packaging, marking, labeling of dangerous goods in accordance with the legislation, whichever is possible according to the type.
- **2.1.3** Ensures that dangerous goods are loaded, stowed, securely connected, transported and unloaded safely in the packaging and load-carrying unit, whichever is possible according to the type of cargo, approved and in accordance with the rules.

2.2 Responsibilities of the port facility operator

2.2.1. Does not dock the ships carrying dangerous goods without the permission of the port authority.

2.2.2 Provides written information to the ship that will dock at its facility in accordance with the facility rules, cargo handling rules and relevant legislation.

2.2.3 Does not handle dangerous cargoes that it does not have permission to handle from the administration, and it does not victimize ships that will dock by planning in this context.

2.2.4 It requests mandatory documents, information and documents related to dangerous goods from the cargo person and ensures that they are included with the cargo. If the relevant documents, information and documents cannot be provided by the cargo person concerned, they are not obliged to accept or handle the dangerous cargo at the facility.

2.2.5 It performs the loading or unloading operation according to the agreement to be reached by sharing all the data that may be required according to the characteristics of the cargo with the ship's relevant person. Operations are not changed without the knowledge of the ship's relevant person.

2.2.6 It determines the operating limits, taking into account the safe working capacity of its facility and weather forecasts, and takes the necessary measures to ensure that the ship is safely connected and handled at the dock.

2.2.7 It checks the transport document containing information that dangerous goods arriving at its facility are properly classified, packaged, marked, labeled, and safely loaded into the freight transport unit.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	18	
	DANGEROUS CARGO HANDLING GUIDE					

2.2.8 It ensures that the personnel involved in the handling of dangerous goods and the planning of this handling are certified by receiving the necessary trainings and does not assign personnel without documents to these operations.

2.2.9 It ensures that the hazardous cargo handling equipment at its facility is in working order and that the relevant personnel are trained and certified regarding the use of these equipment.

2.2.10 It ensures that personnel use personal protective equipment in accordance with the physical and chemical characteristics of the dangerous load by taking occupational safety measures at the coastal facility.

2.2.11 It carries out activities related to dangerous goods at docks, wharves and warehouses established in accordance with these works.

2.2.12 It equips the docks and piers reserved for ships that will load or unload dangerous liquid bulk cargoes with installations and equipment of a suitable nature for this work.

2.2.13 It keeps an up-to-date list of all dangerous goods on ships berthed at its facility and in closed and open areas at its facility and provides this information to interested parties if requested.

2.2.14 It informs the port authority of the immediate risk posed by dangerous cargoes that it handles or temporarily stores at its facility and the measures it takes to do so.

2.2.15 It notifies the port authority of accidents related to dangerous goods, including accidents at the entrance to closed areas.

2.2.16 It provides the necessary support and cooperation in the controls and inspections carried out by the administration and the port authority.

2.2.17 It ensures the transportation of Class 1 (except Class 1 Compliance Group 1.4 S), Class 6.2 and Class 7 dangerous goods that are not allowed to be stored temporarily as soon as possible out of the coastal facility without waiting, and in cases where waiting is necessary, it applies to the Administration for permission.

2.2.18 It stores the cargo transportation units in which dangerous goods are transported temporarily in accordance with the separation and stacking rules, and takes fire, environmental and other safety measures in accordance with the class of dangerous goods in the storage area. It keeps fire extinguishing systems and first aid units ready for use at any time in areas where dangerous loads are handled and conducts the necessary checks periodically.

2.2.19 It receives permission from the port authority before hot working works and operations to be carried out in areas where dangerous cargoes are handled and temporarily stored.

2.2.20 Prepares an emergency evacuation plan for the evacuation of ships from coastal facilities in case of emergency, submits it to the port authority and informs the relevant persons about the plan found appropriate by the port authority.

2.2.21 It ensures that the internal loading of the load-carrying units is carried out in accordance with the loading safety rules at the facility.

2.3 **Responsibilities of the ship's master**

2.3.1 Responsibilities of the ship's master are stated below:

2.3.2 Ensures that the cargo that the ship will carry is certified as suitable for transportation and that the cargo holds, cargo tanks and cargo handling equipment are in a condition suitable for cargo transportation.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	19		
	DANGEROUS CARGO HANDLING GUIDE						

2.3.3 Requests all mandatory documents, information and documents related to dangerous goods from the cargo person and ensures that they are present with the cargo during the transportation activity.

2.3.4 Ensures that the documents, information and documents required to be found on the ship regarding dangerous goods within the scope of legislation and international conventions are appropriate and up-to-date.

2.3.5 Checks the transport document containing information that the cargo handling units loaded on board are properly marked and safely loaded.

2.3.6 Informs the relevant ship personnel about the risks of dangerous cargo, safety procedures, safety and emergency measures, response methods and similar issues.

2.3.7 Keeps up-to-date lists of all dangerous goods on board and declares them to the relevant persons upon request.

2.3.8 Ensures that the loading program, if any, is approved and documented and kept in working condition.

2.3.9 Informs the port authority and the coastal facility of the immediate risk posed by dangerous cargoes on board the ship docking at the coastal facility and the measures it has taken to address it.

2.3.10 Does not accept to carry the dangerous load if there is a leak in the dangerous load or if there is such a possibility.

2.3.11 Notifies the port authority of dangerous cargo accidents that occur on its ship during navigation or while it is at a coastal facility.

2.3.12 It provides the necessary support and cooperation in the controls and inspections carried out by the administration and the port authority.

2.3.13 It does not accept to carry dangerous cargoes that are not included in the ship certificates issued by the relevant institutions and organizations.

2.3.14 Ensures that ship people involved in the handling of dangerous goods use personal protective equipment that meets the physical and chemical characteristics of the cargo during handling.

2.3.15 Provides the requirements for the safety of loading of cargo loaded onto ships.

2.4 **Responsibilities of the Carrier**

2.4.1 Requests all mandatory documents, information and documents related to dangerous goods from the cargo person and ensures that they are present with the cargo during the transportation activity.

2.4.2 Checks the compliance of the dangerous goods classified, packaged, marked, labeled and plated by the cargo person with the legislation.

2.4.3 Checks that dangerous goods are packed in accordance with the rules using approved packaging and load-carrying units, safely loaded into the load-carrying unit and securely connected._

2.5 Responsibilities of the Dangerous Goods Safety Consultant

2.5.1 Follow the compliance with the requirement to the transport of the dangerous goods..

2.5.2 Provide recommendations with regard to the transportation of hazardous materials to the port facility.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	20	
	DANGEROUS CARGO HANDLING GUIDE					

2.5.3 Prepare an annual report on the dangerous goods transportation activities of the facility operator to the port facility.(Annual reports are kept for years and submitted to the authorities upon request.)

2.5.4 Check the applications and methods described below;

2.5.4.1 Procedures regarding to appropriate identification of hazardous substances delivered to the facility, correct use of shipping names of dangerous cargo, certification, packaging, labeling and declaration, inspection on loading and transport of dangerous goods in the certified and proper package, container or cargo unit in a safety way and reporting of inspection results.

2.5.4.2 Loading / unloading evacuation procedure related to handled and temporary dangerous goods,

2.5.4.3 Check that if the port facility considers the special requirements relating to dangerous goods while purchasing means of conveyance regarding to the handled dangerous goods.,

2.5.4.4 Control methods of transport equipment used in loading and unloading of hazardous substances,

2.5.4.5 Including the amendments to the legislation, to check that whether the port facility personnel has necessary training and whether the records of this training is available,

2.5.4.6 Convenience of the emergency methods to be applied in case of occurrence of an accident or incident that may effect the safety during the transport, loading or unloading of the dangerous goods.,

2.5.4.7 Convenience of the reports prepared on the serious accidents, incidents or serious infringements occurring during the transport, loading and unloading of the dangerous substances,

2.5.4.8 Determine the necessary precautions for the possibility of the re-occurrence of the accidents, incidents or serious violations and evaluation of the practices,

2.5.4.9 Check what extent the requirements of the transport of the dangerous good are considered among the selection of the sub-contractor,

2.5.4.10 Determine whether the personnel has detailed knowledge on operational procedures and instructions for the transportation, handling, storage and shipment / discharge of hazardous substances,

2.5.4.11 Convenience of the measures taken for the transportation, handling, storage and shipment / discharge of hazardous substances

2.5.4.12 Procedures on the identification of all necessary documents, information and certifications relating to hazardous materials.

2.5.4.13 Procedures on berthing, loading / unloading, sheltering or anchoring of ships carrying dangerous substances to the port facility day and night safely.

2.5.4.14 Procedures on the additional measures to be taken for loading and unloading of the dangerous goods according to the seasonal conditions.

2.5.4.15 Procedures on fumigation, gas metering and degasification operations. Procedures on keeping records and statistics of hazardous materials,

2.5.4.16 Accuracy of the matters related to the ability and capacity of the port facility for respond to emergencies,

2.5.4.17 Convenience of the regulations for early intervention for accidents involving hazardous substances,

2.5.4.18 Procedures on handling and disposal of damaged dangerous goods and wastes contaminated with dangerous goods,

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	21	
	DANGEROUS CARGO HANDLING GUIDE					

2.5.4.19 Information for the personal protective clothing and procedures among their use.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	22	
	DANGEROUS CARGO HANDLING GUIDE					

3 POLICIES/APPLIED RULES AND MEASURES TO BE FOLLOWED BY PORT FACILITY

3.1 Berthing

- 3.1.1 Adequate and safe mooring facilities are provided; and
- 3.1.2 Adequate safe access is provided between the ship and the shore.

3.2 Supervision

3.2.1 The port operator should ensure that areas where packages or cargo transport units are kept are properly supervised and packages or cargo transport units are regularly inspected for leakage or damage. Any leaking package or cargo transport units should only be handled under the supervision of a responsible person.

3.2.2 The port operator should ensure that no person, without reasonable cause, opens or otherwise interferes with any freight container, tank-container, portable tank or vehicle containing dangerous cargoes. When a freight container, tank-container, portable tank or vehicle is opened by a person authorized to examine its contents, the port operator should ensure that the person concerned is aware of the possible hazards arising from the presence of the dangerous cargoes.

3.2.3 Any equipment which is used for handling and stowing processes and driven with or without power shall be checked and inspected to ensure that it is manufactured in accordance with the manufacturer's instructions and exists in good operating conditions and in compliance with proper standards.

3.3 Identification, packing, marking, labelling or placarding and certification

3.3.1 The port operator should ensure that dangerous cargoes entering his premises have been duly certified or declared by the cargo interests as being properly identified, packed, marked, labelled or placarded so as to comply with the appropriate provisions of the IMDG Code or, alternatively, with appropriate national or international legal requirements applicable to the relevant mode of transport.

3.4 Safe handling and segregation

3.4.1 A port operator transporting or handling dangerous cargoes should appoint at least one responsible person who has adequate knowledge of the national or international legal requirements concerning the transport and handling of dangerous cargoes, including the segregation of incompatible cargoes.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	23	
	DANGEROUS CARGO HANDLING GUIDE					

3.5 Emergency procedures

3.5.1 The port operator should ensure that appropriate emergency arrangements are made and brought to the attention of all concerned. These arrangements should include: **3.5.1.1** the provision of appropriate emergency alarm operating points;

3.5.1.2 procedures for notification of an incident or emergency to the appropriate emergency services within and outside the port area;

3.5.1.3 procedures for notification of an incident or emergency to the port authority and port area users both on land and water;

3.5.1.4 the provision of emergency equipment appropriate to the hazards of the dangerous cargoes to be handled;

3.5.1.5 co-ordinated arrangements for the release of a ship in the case of an emergency; and

3.5.1.6 arrangements to ensure adequate access/egress at all times.

3.5.2 The port operator should consider the necessity of arrangements for a safe and quick emergency escape, taking into account the nature of the dangerous cargoes and any special conditions.

3.5.3 The "Medical First Aid Guidelines (MFAG)" annexed to IMDG Code shall be used to provide with those persons effected from damages caused by hazardous loads with medical first aid in case of any health issues occurring in consequence of accidents involving such loads.

3.5.4 "Emergency Schedules (EmS)" annexed to IMDG Code shall be used for any emergencies involving hazardous loads.

3.5.5 In case of any emergencies or accidents, the first aid material to be used for response shall be kept in easily accessible locations known to personnel.

3.6 Emergency information

3.6.1 The port operator should ensure that a list of all dangerous cargoes in the warehouses, sheds or other areas, including the quantities, and if appropriate Proper Shipping Names, correct technical names (if applicable), UN numbers, classes or, when assigned, the division of the goods, including for class 1, the compatibility group letter, subsidiary hazard classes (if assigned), packing group (where assigned) and exact location is held readily available for the emergency services.

3.6.2 The port operator should ensure that the responsible person for a warehouse, shed or area, where dangerous cargoes are handled, is as far as possible aware of the status of occupancy with the dangerous cargoes in his area and is available in case of emergencies.

3.6.3 The port operator should ensure that the person responsible for cargo handling operations involving dangerous cargoes has the necessary information on measures to be taken to deal with incidents involving dangerous cargoes and that it is available for use in emergencies.

3.6.4 Electronic or other automated information processing or transmission techniques shall be employed to provide access to information.

3.6.5 Data sheets of hazardous materials shall normally be kept by the manufacturers of chemicals. Emergency response information and electronic databases shall be available and used in case of direct access to information.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	24	
	DANGEROUS CARGO HANDLING GUIDE					

3.6.6 The port operator should ensure that the port or berth emergency response procedures and port or port emergency telephone numbers are placed at prominent locations within or at warehouses, sheds or areas where dangerous cargoes are transported or handled.

3.6.7 The port operator should ensure that fire-fighting and pollution-combating equipment and installations are clearly marked as such and notices drawing attention to them are clearly visible at all appropriate locations.

3.6.8 The port operator should inform the master of any ship carrying or handling dangerous cargoes of the emergency procedures in force and the services available at the port.

3.7 Fire precautions

3.7.1 The port operator should ensure that:

3.7.1.1 All parts of the port and any ship moored to it are at all times accessible to emergency services;

3.7.1.2 Audible or visual alarms for emergency use are installed in the area or other means of rapid communication with emergency services are available;

3.7.1.3 The handling of dangerous cargoes are kept clean and tidy;

3.7.1.4 Before dangerous cargoes are handled, the master of a ship is informed of the location of the nearest means of summoning emergency services; and

3.7.1.5 the lighting and other electrical equipment in areas where dangerous cargoes are present on the port is of a type safe for use in a flammable or explosive atmosphere. **3.7.1.6** Places where smoking is prohibited are designated; and

3.7.1.7 Notices in a pictogram form prohibiting smoking are clearly visible at all locations and at a safe distance from places where smoking would constitute a hazard. **3.7.1.8** The port operator should ensure that equipment used in an area or space where a flammable or explosive atmosphere may exist or develop, is of a type safe for use in

a flammable or explosive atmosphere and used in such a manner that no fire or explosion can be caused.

3.7.1.9 The port operator should ensure that only portable electrical equipment of a type safe for use in a flammable atmosphere is used in an area or space in which a flammable atmosphere may occur.

3.7.1.10 The port operator should ensure that electrical equipment on a wandering lead is not used in areas or spaces where a flammable atmosphere may occur.

3.8 Fire fighting

3.8.1 The port operator should ensure that adequate and properly tested fire-fighting equipment and facilities are provided and readily available in accordance with the requirements of the regulatory authority in areas where dangerous cargoes are transported or handled.

3.8.2 The port operator should ensure that personnel involved in the handling or transport of dangerous cargoes are trained and practised in the use of fire-fighting equipment in accordance with the requirements of the regulatory authority.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	25	
	DANGEROUS CARGO HANDLING GUIDE					

3.9 Environmental precautions

3.9.1 The port operator should ensure that dangerous cargoes are only handled in areas which comply with the requirements of the regulatory authority.

3.9.2 The port operator should ensure that any damaged package, unit load or cargo transport unit containing dangerous cargoes is dealt with in accordance with the requirements of the regulatory authority and is not transported or handled unless the dangerous cargoes have been properly repacked and are in all respects fit and safe for further transport and handling.

3.9.3 The port operator should ensure that, if necessary, any damaged package, unit load or cargo transport unit containing dangerous cargoes is removed to a designated area for such cargoes.

sweeping or flushing. The said loads shall not be allowed to move into sea by rainwater. **3.9.5** During the loading and unloading of bulk cargo to and from the vessel, necessary actions shall be taken to prevent the dumping of any load from the vessel or the dock into sea. In addition, these actions shall be taken for transshipment operations. **3.9.6** Necessary actions shall be taken so that soil, water or areas of water discharge is/are not contaminated with any hazardous materials handled at onshore facilities. Additionally, these actions shall be applied for the piping line used during the handling

of hazardous materials and for areas with conveyor system.

3.9.7 The capability to remove any contaminated bilge water, dirty ballast, sludge, slope and load waste from the vessel shall be provided.

3.10 Pollution combating

3.10.1 The port operator should ensure that adequate equipment is available to minimize the damage in case of a spillage of dangerous cargoes.

3.10.2 The equipment includes petroleum dispersion preventive fences, condensate lids, absorbing and neutralizing agents as well as cleaning agents and portable collection basins.

3.10.3 The port operator should ensure that personnel involved in the transport and handling of dangerous cargoes are trained and practised in the use of pollution combating equipment and facilities in accordance with the requirements of the regulatory authority.

3.11 Reporting of incidents

3.11.1 The port operator, within his area of responsibility, should ensure that, if an incident occurs during the handling of dangerous cargoes which may endanger the safety or security of persons, of ships within the port, of the port or of any other property, or the environment, the person having charge of the handling immediately causes the operation to be stopped, if it is safe to do so, and prevents it being resumed until appropriate safety measures have been taken. The port operator should require every member of his personnel to report, to the person having charge of the operation, any such incident they see to occur during the handling of dangerous cargoes.

3.11.2 For the purposes of responding quickly and effectively; the short and proper description of the event should be communicated to the emergency center as soon as possible to treat the injured personnel and mitigate any potential damage.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	26	
	DANGEROUS CARGO HANDLING GUIDE					

3.11.3 The port operator should ensure that any incident involving dangerous cargoes which may endanger the safety or security of persons, or of ships within the port or of the port or of any other property or the environment is reported immediately to the port authority.

3.11.4 The port operator should ensure that any damaged or leaking package, unit load or cargo transport unit containing dangerous cargoes is reported immediately to the port authority and that suitable remedial action is taken

3.12 Inspections

3.12.1 The port operator, where appropriate, should:

3.12.1.1 Check documents and certificates concerning the safe transport, handling, packing and stowage of dangerous cargoes in the port area at the time of receipt;

3.13.1.2 Check, where practicable, packages, unit loads and cargo transport units containing dangerous cargoes to verify that they are marked, labelled or placarded in accordance with the provisions of the IMDG Code and the appropriate national or international legal requirements applicable for the mode of transport and that unnecessary labels, placards and marks have been removed and that the cargo transport units have been loaded, packed and secured in accordance with the IMO/ILO/UN ECE Guidelines for Packing of Cargo Transport Units (CTUs);

3.13.1.3 Check freight containers, tank-containers, portable tanks and vehicles containing dangerous cargoes to ensure that they have a current safety approval plate in accordance with the International Convention for Safe Containers (CSC), 1972, as amended, when applicable, or have been approved in accordance with the relevant provisions of the IMDG Code or by a certification or approval system of an appropriate authority; and

3.13.1.4 Check, by external examination, the physical condition of each freight container, tank-container, portable tank or vehicle containing dangerous cargoes for obvious damage affecting its strength or packaging integrity and for the presence of any sign of leakage of contents.

3.13.2 The port operator should make such checks regularly to ensure implementation of the safety precautions in the port area and the safety of transport.

3.13.3 If any of the checks mentioned above reveal deficiencies which may affect the safe transport or handling of dangerous cargoes the port operator should immediately advise all parties concerned and request them to rectify all deficiencies prior to any further transport or handling of dangerous cargoes.

3.13.4 The port operator should ensure that every necessary support will be given to the port authority or any other person or institution entitled to carry out inspections when they intend to carry out an inspection of dangerous cargoes.

3.13 Hot work and other repair or maintenance work

3.13.1 The port operator should ensure that no repair or maintenance work resulting in non-availability of the emergency/fire equipment required by these Recommendations is carried out at the port without prior permission of the port authority.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	27	
	DANGEROUS CARGO HANDLING GUIDE					

3.13.2 The port operator and the company carrying out the repairs, after having consulted the master of a ship, where appropriate, should ensure that they are in possession of a permit to proceed issued by the port authority before any repair or maintenance work involving hot work, or any other such work which may lead to a hazard because of the presence of dangerous cargoes, is carried out.

3.13.3 A prior notice to be served for the estimated duration of hot work or the lack of equipment as a result of the need for permission shall allow all emergency response authorities, such as fire department, to make a satisfactory announcement to express their objection and recommend additional measures. In case of particular circumstances, such as any hot work to be performed in a hold or closed areas near a hold, the skilled personnel capable of determining whether specific safety measures are necessary shall perform a detailed field survey.

3.14 Contaminated wastes

3.14.1 The port operator should ensure that wastes contaminated with dangerous cargoes are immediately collected and disposed of in accordance with the requirements of the regulatory authority.

3.15 Alcohol and drug abuse

3.151 The port operator, within his area of responsibility, should ensure that no person under the influence of alcohol or drugs is allowed to participate in any operation involving the handling of dangerous cargoes.

3.16.2 Any such persons should always be kept clear of the immediate areas where dangerous cargoes are being transported or handled.

3.16 Training

3.16.1 The personnel who are in charge of actions and operations for the loading/unloading of hazardous materials at the onshore facility shall be provided with training on emergencies (fire, explosion, leakage etc.) and response, occupational health and safety, ISPS code security awareness and safety in line with their job descriptions and fields of work.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	28	
	DANGEROUS CARGO HANDLING GUIDE					

4 CLASSIFICATION OF DANGEROUS GOODS, HANDLING, LOADING / UNLOADING, HANDLING, SEPARATION, STACKING AND STORING

4.1 Classification of Dangerous Goods

As explained in IMDG Code Volume 1 Chapter 2, Dangerous Goods Classes and Subdivisions are as follows:

IMDG	Danger	Name of The Class
Code		
2.0		General
2.1	Class 1	Explosives
2.2	Class 2	Gases
2.3	Class 3	Flammable Liquids
2.4	Class 4.1	Flammable solids, self-reactive substances, polymerizing agents and solid desensitized explosives
	Class 4.2	Substances liable to spontaneous combustion
	Class 4.3	Substances which, in contact with water, emit flammable gases
2.5	Class 5.1	Oxidizing substances
	Class 5.2	Organic Peroxides
2.6	Class 6.1	Toxic substances
	Class 6.2	Infectious substances
2.7	Class 7	Radioactive materials
2.8	Class 8	Corrosive Substances
2.9	Class 9	Miscellaneous dangerous cargoes and objects

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	29		
	DANGEROUS CARGO HANDLING GUIDE						

Hazardous cargo Subdivisions:

Class 1 Explosives:

Class 1.1 Explosives with mass destruction capacity

Class 1.2 Explosives without mass destruction capacity but with fragmentation effect

Class 1.3 Explosives that will not have a mass destruction effect but will cause fire or partial fragmentation or explosion or both

Class 1.4 Substances without significant explosion hazard

Class 1.5 Substances with mass destruction effect but not very sensitive

Class 1.6 Substances without mass destruction capacity and not very sensitive

The subdivisions from most hazardous to least hazardous are as follows: 1.1, 1.5, 1.2, 1.3, 1.6, 1.4. There are Compatibility Groups for each Subdivision (IMDG Code Section 2.1.2). The meaning of the Compatibility Groups and the Subsection to which they are compliant are explained below:

a) Primary explosive substance (1.1)

b) Articles containing a primary explosive substance and not containing two or more effective protective features. Some articles such as detonators for detonating, detonators for bursting and initiating charges, detonators of the type, are included even if they do not contain a primary explosive (1.1, 1.2, 1.4).

c) Propelling explosives or other detonating explosive substances or articles containing such explosive substances (1.1, 1.2, 1.3, 1.4)

d) Articles containing explosives used in secondary detonation or black powder or secondary detonating explosives; in each case, substances or articles which do not detonate without the means of initiation and the propelling charge, the primary explosive and the article containing two or more effective protective features (1.1, 1.2, 1.4, 1.5)

e) Articles containing secondary detonating explosives without means of initiation, with propelling charge (excluding flammable liquids or gels or hypergolic liquids) (1.1, 1.2, 1.4)

f) Articles containing secondary detonating explosives capable of initiating ignition, with propelling charge (excluding flammable liquids or gels or hypergolic liquids) or without propelling charge (1.1, 1.2, 1.3, 1.4).

g) Pyrotechnic substance or article containing pyrotechnic substance or article containing both explosive substance and illuminating, incendiary, tear or smoke producing substance, (excluding water-reactive object or white phosphorus, phosphides, pyrophobic substance, flammable liquid or gel, or hypergolic liquids) (1.1, 1.2, 1.3, 1.4)

h) Article containing both explosive substance and white phosphorus (1.2, 1.3)

i) Article containing both explosive substance and flammable liquid or gel (1.1, 1.2, 1.3)

j) Article containing both explosive substance and toxic chemical substance (1.2, 1.3) k) Explosive substance or article containing explosive substance and presenting a special risk (e.g. presence of water-reactive or hypergolic liquid, phosphides or pyrophobic substances) and each type requiring isolation (1.1, 1.2, 1.3)1) Articles containing only extremely insensitive substances (1.6)

m) Substances or articles so packaged or designed that the hazardous effects of

accidental activation are confined to the interior of the package and that, even if the package loses its properties as a result of fire, all explosion and dispersion effects do
LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	30		
	DANGEROUS CARGO HANDLING GUIDE						

not significantly impede fire-fighting or other emergency response efforts in the immediate vicinity of the package (1.4)

Class 2 Gases

Class 2.1 Flammable Gases

Class 2.2 Non-flammable and Non-toxic Gases

Class 2.3 Toxic Gases

Class 3 Flammable Liquids

Class 4 Flammable Solids

Class 4.1 Flammable Solids

Class 4.2 Spontaneous Combustion Solids

- Class 4.3 Solids which, in Contact with Water, emit Flammable Gases
- Class 5 Oxidizing Substances and Organic Peroxides
- Class 5.1 Oxidizing Substances
- Class 5.2 Organic Peroxides
- Class 6 Toxic and Infectious Substances
- Class 6.1 Toxic Substances

Class 6.2 Infectious Substances

There are no Subdivisions for Class 3, Class 7, Class 8 and Class 9.

4.2 Dangerous Goods Packing and Packages

Markings, labels and/or placards on products are all channels of communication to the user.

These communication channels will tell the user the characteristics of a consignment or product. The IMDG Code provides clear procedures related to authorization of consignments as well as advance notification, markings, labels and documentation (by manual, electronic data processing or electronic data interchange techniques and placarding).

The code specifies clearly that no person may offer to transport dangerous goods unless the goods are properly marked, labeled, placarded, described and certified on a document. Those who are transporting dangerous goods must indicate the UN Number and proper shipping name clearly on the consignment. In the case of marine pollutants, the word "marine pollutant" must be on the document accompanying the consignment. This requirement is particularly important in the case of an accident involving these goods, in order to determine what emergency procedures are necessary to deal properly with the situation. In the case of marine pollutants, the captain of the vessel needs to comply with the requirements of MARPOL 73/78.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	31
	DANGEROUS CARGO HANDLING GUIDE				











LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	32	
	DANGEROUS CARGO HANDLING GUIDE					

4.3 Dangerous Goods Marking, Labels, Placards.

The IMDG Code recommends a system based on labels and placards designed especially so that all who work close to this type of cargo will be able to recognize, preferably at first sight, the nature of the risks entailed by these substances, whatever their packaging might be.

4.3.1 Labels

The IMDG Code states that all packaging, packages and drums carrying dangerous goods must be labeled. The labels are in the shape of a rhombus in white, orange, blue, green or red, or a combination of these colors. Symbols illustrating the danger of the class are also required. In general, each label is divided into two parts, the bottom half and the top half. The top half is for the symbol of the class of the good(s), and the lower half is for the text, class or division number. The minimum dimensions of labels are 10 cm x 10 cm. Labels must be firmly adhered to and placed on the package so that it can easily be seen. The quality of the labels must be such so they do not deteriorate outdoors and remain unaltered during the complete transport period and at least three months in the sea.

Due to the fact that dangerous goods can pose more than one risk, it is also necessary to use "secondary risk labels". These labels are the same as the ones showing the primary risk, regarding their color, shape and symbols. Even though the IMDG Code says nothing to this effect, in some countries the class number is only indicated in the primary risk label, and that the secondary risk label does not include the class number. This is an effective way to distinguish between both.

4.3.2 Placards

The IMDG Code determines that all "cargo transport units" containing dangerous goods must be placarded. In this context, cargo transport units are containers, containers for liquids, tank vehicles, vehicles transporting goods by land, railway wagons with water tanks, good tanks destined for intermodal transport. Placards have the same shape, colors and symbols as the labels, but their dimension is 25 x 25 cm. Containers carrying more than 4000 kilograms of dangerous goods, and all tanks for liquids and gases must have the "United Nations number". The UN number has four digits and is the number assigned by the United Nations to all goods identified and classified as dangerous.

Containers carrying dangerous goods must display at least one placard on each side and one on each end of the unit (this is to say, on its four sides)

Rail wagons must be placarded on at least both sides

Freight containers, semi-trailers and portable tanks must be placarded on all four sides

Road vehicles must display appropriate placards on both sides as well as the rear

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	33	
	DANGEROUS CARGO HANDLING GUIDE					

Shapes and Colors of Labels and Placards Class 1 – Explosives

A	Division 1.1 / 1.2 / 1.3
	Symbol – explosion in black color
1 Star	Background – orange color
1-574-	Text – Explosive (optional)
	** Location of division and/or Compatibility Group
· · · ·	* Location of Compatibility Group or text
	Number 1 – in the bottom corner
1.4	Division 1.4 / 1.5 /
1.5	1.6 Background –
1.6	orange color
	Subclass numbers – in black color (approximately 30
··· /	mm x 5 mm in labels of 100 mm x 100 mm)
1	* Location of Compatibility Group
-	Number 1 – in the bottom corner

Class 2 – Gases

(No.2.1)	Division 2.1 Flammable Gases Symbol – Flame in black or white Background – in red color Text – Flammable Gas (optional) Number 2 – in the bottom corner
(No.2.2)	Division2.2Non-flammablegasesSymbol – Gas cylinder inblack or white colorBackground – in green colorText – Non flammablecompressed gas (optional)Number 2 – in the bottom corner
2	Division 2.3 Toxic Gases Symbol – skull and crossbones in black color Background – in white color Text – Toxic (optional) Number 2 – in the bottom corner

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	34	
	DANGEROUS CARGO HANDLING GUIDE					

Class 3 – Flammable Liquids



Class 4 – Flammable Solids; Substances liable to spontaneous combustion;
substances which, in contact with water emit flammable gases

Division 4.1 Flammable Solids Symbol – flame in black color Background – white with seven red vertical stripes Text – Flammable Solid Number 4 – In the bottom corner		
Division 4.2 Substances liable to spontaneous combustion Symbol – flame in black color or white color Background – blue color Text – Spontaneous combustion substances (optional) Number 4 – in the bottom corner		
Division 4.3 Substances which, in contact with water, emit flammable gases Symbol – flame in black or white color Background – blue color Text – Substances which, in contact with water, emit flammable gases (optional) Number 4 – in the bottom		

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	35
	DANGEROUS CARGO HANDLING GUIDE				

Class 5 – Oxidizing Su	bstances or Organic Peroxides
	Division 5.1 Oxidant Substances
	Symbol – flame with circle in black
	color Background – yellow color
	Text – Oxidizing Substance (optional)
	Number 5.1 – in the bottom corner
5.1	
	Division 5.2 Organic
	Peroxides Symbol – flame
	in white color Top Half – red
	Bottom Half – yellow
	Text – Organic Peroxide (optional)
	Number 5.2 – in the bottom corner
5.2	
· · · · · · · · · · · · · · · · · · ·	

Class 6 – Toxic Substances or Infectious Substances



Division 6.1 Toxic Substances Symbol – black skull and crossbones Background – white color Text – Toxic (optional) Number 6 – in the bottom corner

Class 8 – Corrosive Substances



Symbol – Liquids falling from two test tubes onto a hand and a black piece of metal Background – Upper half in white color and lower half in black with white borders Text – Corrosive (optional) Number 8 – In the bottom corner

	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	36	
	DANGEROUS CARGO HANDLING GUIDE					

Class 9 – Miscellaneous Dangerous Substances and Articles Potentially Damaging to the Environment



Symbol – seven vertical bars in black in the upper half Background – in white color Number 9 – In the bottom corner

Other labels

Other Jubers	
	Indicating elevated temperature (liquid state at a temperature equal to or exceeding 100°C, in a solid state at a temperature equal to or exceeding 240°C)
	Orange-colored plates, with hazard-identification number and UN Number
	Orientation arrows, black or red color
Placards for Mari	ine Pollutants



Packages and cargo transport units containing dangerous substances which are classified by the IMDG Code as "marine pollutants", must have the markings shown here, which must be durable. They must be placed close to the risk labels or risk placards of the goods. The dimensions of the marine pollutant markings must be a minimum of 10 cm per side for packages and 25 cm per side for cargo transport units.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001	37							
	DANGEROUS CARGO HANDLING GUIDE								

4.4 Packaging and Approval Marking.

4.4.1 Packing Groups, Classifying Criteria

The risks presented by dangerous goods in maritime transport are related to their packaging, therefore it must be safe, well designed and manufactured and in good condition. It is very unlikely you will suffer injuries due to this cargo, but if the cargo is damaged, it is possible for dangerous substances or vapors to be released.

The packages/containers must comply with the following requirements:

Must not be affected by the cargo it contains

Must be strong enough to endure the rough treatment and risks involved in maritime transport

Must be able to endure rain, wind and sea water Must be practical and adequate for the cargo they carry Must be in good condition Must be correctly marked, label and signposted

For packing purposes, dangerous goods belonging to all classes, except for class 1, 2, 6.2 and 7 have been divided into three "packing groups" depending on the degree of danger they represent:

Packing Group I –	High level of danger
Packing Group II –	Medium level of danger
Packing Group III –	Low level of danger

4.4.2 UN Packaging and Approval Marking

Most packages also need to bear the UN packaging approval mark confirming that the packaging has been tested and approved in accordance with relevant United Nations performance standards. Example below:



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001	02.06.2022	3	16.05.2025	38				
	DANGEROUS CARGO HANDLING GUIDE								

4.5 **Segregation and Separation**

One of the most important aspects of managing the transport of dangerous goods is the stowage, segregation and separation of these goods. Hazardous substances must not be carried with goods which are liable to interact and cause danger to P.E.A.R.

Incompatible hazardous substances must be adequately separated from each other during transport and storage. Improper stowage or segregation of dangerous goods may result in the release of toxic fumes, fire, spill and degradation of the product's quality. For this reason the IMDG Code has provided provisions in Volume 1 Part 7 titled "Provisions Concerning Transport Operations", which focuses on stowage and segregation.

4.5.1 **Principles of segregation and stowage**

The following issues may contribute towards major chemical accidents during stowage and segregation:

Failure to understand the nature of the substance handled Failure of quality assurance – container inspection certificates

Insufficient recording of chemical register inventories at different terminal locations

Insufficient labeling and recording of chemicals Poor housekeeping – firefighting equipment not available in work area

The IMDG Code requires dangerous goods to be stored and segregated according to the hazard, class and compatibility. The code also provides detailed information on these important factors in terms of where dangerous goods should be stowed and how they should be separated or segregated from other cargoes.

Although the IMDG Code provides detailed information on ship stowage, the requirements can also be applied to storage ashore and even to container packing. The requirement offers a framework for port authorities when preparing their regulations for the safe transport of handling and storage of dangerous goods in ports. Dangerous goods which have to be segregated from each other shall not be transported in the same cargo transport unit.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001	02.06.2022	3	16.05.2025	39				
	DANGEROUS CARGO HANDLING GUIDE								

4.5.2 IMDG Code segregation, stowage and Dangerous Goods list

General segregation is applied to all cargo spaces on deck or under deck of all types of ships and cargo in transport units and incompatible goods shall be segregated from one another. For the purpose of segregation, the IMDG Code has grouped together similar chemical properties in the dangerous goods list. In the dangerous goods list, the group substances are referred as follows:

- 1. Acids
- 2. Ammonium Compound
- 3. Bromates
- 4. Chlorates
- 5. Chlorites
- 6. Cyanides
- 7. Heavy metals and their salts
- 8. Hypochlorite
- 9. Lead and its compounds
- 10. Liquid halogenated hydrocarbons
- 11. Mercury and mercury compounds
- 12. Nitrites and their mixtures
- 13. Perchlorates
- 14. Permanganates
- 15. Powdered metals
- 16. Peroxides
- 17. Azides
- 18. Alkalis

If substances are shipped under Not Otherwise Specified (N.O.S.) entries, the shipper will decide the appropriate segregation group.

In the IMDG code Volume 2 under column 16 of the numerical list of dangerous goods, the stowage conditions for each one of the dangerous goods listed can be found. Also, in this column, there is information on stowage related to sleeping, food, solutions and mixtures areas, etc. For example, the product "ALLYL BROMIDE UN No 1099", column 16 indicates "Category B, far from living quarters."

In the following paragraph the five stowage categories stipulated by the IMDG Code are described.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001	02.06.2022	3	40					
	DANGEROUS CARGO HANDLING GUIDE								

Stowage Categories

Category	egory A B C				Ε
Cargo ship carrying no more than 25 passengers	On deck or below deck	On deck or below deck	On deck only	On deck only	On deck or below deck
Passenger ships carrying more than 25 passengers	On deck or below deck	On deck only	On deck only	Prohibited	Prohibited

Regarding Class 1 (Explosives) the code establishes the following 5 categories for stowage onboard:

Category	Cargo Ships	Passenger Ships				
01	On deck or below deck	On deck or below deck				
02	On deck or below deck	On deck in closed transport				
	On deek of below deek	units or under deck in closed				
03	On deals or below deals	On deck only in closed				
	OII deck of below deck	cargo transport				
04	On deck or below deck	PROHIBITED				
05	On deck in closed cargo transport	On deck in close cargo				
	units or under deck	transport units or				

In brief, the IMDG Code establishes a system whereby dangerous goods can be stowed in a safe way, considering their compatibility with other types of cargo and therefore preventing further damage in case of accidents.

Mastering the techniques on how to stow dangerous goods correctly on board ships is fundamentally the responsibility of the Ship Planner. Port Terminals are not concerned with planning of the stowage of dangerous goods on board; they are only responsible of stowing the cargo in the positions indicated in the ships plan, which is provided by the Shipping Line through the respective agencies.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001	02.06.2022	3	41					
	DANGEROUS CARGO HANDLING GUIDE								

4.6 Separation distances and separation terms for hazardous materials applicable storage at storage area

4.6.1 Segregation Categories

The IMDG Code defines four segregation terms:

"Away from" (the minimum separation between two incompatible goods)

"Separated from"

"Separated by a complete compartment or hold from"

"Separated longitudinally by an intervening complete compartment or hold

from" (this is the maximum separation between two incompatible goods)

The general provisions regarding segregation between different classes of dangerous goods can be found in the code in the following Segregation Table:

CLASS		1.1 1.2 1.5	1.3 1.6	1.4	2.1	2.2	2.3	3	4.1	4.2	4.3	5.1	5.2	6.1	6.2	7	8	9
Explosives	1.1, 1.2, 1.5	*	*	*	4	2	2	4	4	4	4	4	4	2	4	2	4	Х
Explosives	1.3, 1.6	*	*	*	4	2	2	4	3	3	4	4	4	2	4	2	2	X
Explosives	1.4	*	*	*	2	1	1	2	2	2	2	2	2	Х	4	2	2	X
Flammable gases	2.1	4	4	2	Х	X	Х	2	1	2	Х	2	2	Х	4	2	1	X
Non-toxic, non-flammable gases	2.2	2	2	1	x	x	х	1	x	1	х	x	1	x	2	1	x	x
Toxic gases	2.3	2	2	1	Х	X	Х	2	Х	2	Х	Х	2	Х	2	1	Х	Х
Flammable liquids	3	4	4	2	2	1	2	X	Х	2	1	2	2	Х	3	2	Х	Х
Flammable solids (including self-reactive substances and solid desensitized explosives)	4.1	4	3	2	1	x	х	x	х	1	х	1	2	х	3	2	1	X
Substances liable to spontaneous combustion	4.2	4	3	2	2	1	2	2	1	X	1	2	2	1	3	2	1	X
Substances which. in contact with water, emit flammable gases	4.3	4	4	2	x	x	х	1	x	1	x	2	2	x	2	2	1	X
Oxidizing substances (agents)	5.1	4	4	2	2	X	Х	2	1	2	2	X	2	1	3	1	2	X
Organic peroxides	5.2	4	4	2	2	1	2	2	2	2	2	2	X	1	3	2	2	Х
Toxic substances	6.1	2	2	X	Х	X	Х	X	Х	1	Х	1	1	Х	1	X	X	Х
Infectious substances	6.2	4	4	4	4	2	2	3	3	3	2	3	3	1	Х	3	3	X
Radioactive material	7	2	2	2	2	1	1	2	2	2	2	1	2	Х	3	X	2	X
Corrosive substances	8	4	2	2	1	X	Х	X	1	1	1	2	2	Х	3	2	x	X
Miscellaneous dangerous substances and articles	9	X	X	X	X	X	X	x	X	X	X	X	X	X	X	x	x	X

(This table is applied to unitized dangerous goods; this is to say, in pallets, drums, boxes and crates and other similar packaging. It is not applied to containers carrying dangerous goods)

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001	02.06.2022	3	16.05.2025	42				
	DANGEROUS CARGO HANDLING GUIDE								

Numbers and symbols relate to the following terms as defined in this chapter:

1	Away from	3 meters
2	Separated from	6 meters
3	Separated by a complete compartment or hold from	12 meters
4	Separated longitudinally by an intervening complete compartment or hold from	24 meters
X	The segregation, if any, is shown in the Dangerous Goods List	-

Explosives require special segregation in accordance with the compatibility group. Explosives which have the same letter can be stowed together, whatever their class subdivision may be. Since the properties of the substances, materials or articles of a same Class can be very different to each other, in each and every case it will be necessary to consult the Dangerous Goods list previously, to determine the applicable specific segregation provisions.

4.6.2 Segregation within the Cargo Transport Units

Dangerous goods which need to be segregated from each other must not be stowed in the same cargo transport unit (container). Nevertheless, goods which require to be segregated "away from" may be transported in the same cargo transport unit upon authorization by the corresponding authority. In this case an equivalent safety degree must be kept.

4.6.3 Segregation in Port Areas

The IMO Maritime Safety Committee (MSC), by way of Circular 1/1216 of 26 February 2008 determined several revised recommendations regarding the risk free transport of dangerous goods and related activities within the port area.

Circular MSC 1216 of 2008 establishes that containers containing dangerous goods must not be stowed above each other. **Containers carrying dangerous cargo of the same class are exempt from this rule.** This exemption is not to be applied to Class 8 cargo (corrosives), if they are different from each other. This is to say, if the Class 8 corrosive cargo is exactly the same substance, they can be stored above each other. Containers must be stowed in such a way that there is always easy access to the doors and to the sides in order to carry out cooling or control work

Separation between the different classes must be taken into consideration when dangerous goods are stored in special areas or deposits. The chart indicated by IMDG Code will help in the stowage on board ships. IMO's Port Recommendations establishes the following segregation chart for port storage.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	43
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

Classes		2.1	2.2	2.3	3	4.1	4.2	4.3	5.1	5.2	6.1	8	9
Flammable gases	2.1	0	0	0	S	А	S	0	S	S	0	Α	0
Non-toxic,	2.2	0	0	0	А	0	А	0	0	А	0	0	0
non-			Ŭ	Ť		Ť		, in the second se			, in the second	- T	Ŭ
Toxic gases	2.3	0	0	0	S	0	S	0	0	S	0	0	0
Flammable liquids	3	S	Α	S	0	0	S	Α	S	S	0	0	0
Flammable solids, self- reactive substances and	4.1	А	0	0	0	0	А	0	А	S	0	А	0
Spontaneously combustible	4.2	S	А	S	S	А	0	А	S	S	А	А	0
Substances which, in contact with water, emit	4.3	0	0	0	А	0	А	0	S	S	0	А	0
Oxidizing substances	5.1	S	0	0	S	Α	S	S	0	S	Α	S	0
Organic peroxides	5.2	S	Α	S	S	S	S	S	S	0	Α	S	0
Toxic substances	6.1	0	0	0	0	0	А	0	А	А	0	0	0
Corrosives (liquids and solids)	8	А	0	0	0	А	А	А	S	S	0	0	0
Miscellaneous dangerous substances and	9	0	0	0	0	0	0	0	0	0	0	0	0

The chart identifies only three segregation categories for storage in ports.

"0" means pairs of dangerous goods which do not need to be segregated from each other (unless indicated by the individual entry in the numerical list of dangerous goods, which must always be checked, requires so)

"A" indicates segregation requirement "away from ..." the other class in that pair (3 meters)

"S" requires the segregation category "separated from ..." between the classes of that pair (6 meters)

Cargoes of classes 1 (except division 1.4 S), 6.2 and 7 should normally be allowed into the port area for direct shipment or delivery only. These classes have not been included in the table. However, if through unforeseen circumstances, these cargoes have to be temporarily kept, it should be in designated areas. Segregation requirements of the individual class as stipulated in the IMDG Code should be considered by the port authority when establishing specific requirements.

Cleaning of container and portable tanks which contained dangerous goods must be done in a special area, away from to those where dangerous goods are stored. Such areas shall be adequately designed and equipped to avoid contaminated washing water ending up in the soil, waterways or sewerage system.

After deconsolidating (un-stuffing/ stripping) a container with dangerous goods, all placards and goods risk identification shall be removed from the container.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	44
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

5 HANDBOOK OF DANGEROUS GOODS

Dangerous cargo shipment / discharge with handling and port facilities in the temporary storage activities in order to contribute to the fulfillment of these activities in a safe manner;

- Dangerous Goods classes,
- Packages of dangerous substances,
- Packaging,
- Labels,
- Signs and packaging group,
- Ship and port seperation table according to the class of dangerous goods,
- Warehouse / port separation distance of dangerous goods storage,
- Seperation terms,
- Dangerous cargo documentation,
- Dangerous goods emergency response action flow diagram
- Emergency contact information

- A Dangerous Goods Handbook has been prepared in pocket size, containing the locations of emergency equipment, usage instructions and shore facility rules, and presented in the appendix.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	45
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

6 PROCEDURES FOR THE OPERATION

6.1 Prosedure of ships carrying dangerous goods safely Berthing, loading / unloading, shelter or anchorage during the day and at night

6.1.1 It is the responsibility of the harbour master to direct where and when a ship carrying any dangerous cargo on board may anchor, berth with tugboats, or stay in the port area, taking into account relevant issues such as the nature and quantity of the dangerous cargo, the environment, population and weather conditions.

6.1.2 In an emergency, the ship captain may direct the transportation of a ship carrying any dangerous cargo on its deck to the port area or to remove it from the port area for the safety of the ship and crew, with the decision of the port management and the approval of the harbour master.

6.1.3 Attach such requirements to any such directions as are appropriate to local circumstances and the quantity and nature of the dangerous cargoes involved.

6.1.4 The port operator should ensure that:

6.1.4.1 adequate and safe mooring facilities are provided; and

6.1.4.2 adequate safe access is provided between the ship and the shore.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	46
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

6.2 Procedure of according to the seasonal conditions additional measures that Loading/Unloading, limbo operation of dangerous goods should be taken by port facilties

6.2.1 explosives or liquid bulk dangerous cargoes should be handled during thunderstorms nor should unprotected cargoes, which react dangerously when in contact with water, be handled during rain.

6.2.2 Solid bulk dangerous cargoes that, on contact with water, may evolve flammable or toxic vapours or become liable to spontaneous combustion, should be kept as dry as reasonably practicable. Such cargoes should be handled only during dry weather conditions.

6.2.3 Because of the nature of explosives the handling of dangerous cargoes in adverse weather conditions need careful attention, particularly in respect of wet conditions.

6.2.4 In extremely rainy weather, filling / unloading activities are suspended, taking into account personnel safety.

6.2.5 Loading and unloading operations are suspended in case of storms, sudden strong winds or lightning strikes.

6.2.6 In case of snow and ice, port machines and transfer vehicles are not allowed to operate until the slippery environment is eliminated, and when environmental security is ensured, the vehicles perform operations at the safest speed.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	47
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

6.3 Procedures on keeping any inflammable, combustible and explosive materials away from operations which cause or are likely to cause sparking and abstaining from operating any tools, apparatus or device which cause or are likely to cause sparking in areas where hazardous materials are handled, stowed and stored

6.3.1 Before starting any hot work, on board a ship or on a port, the responsible person of the company to carry out the hot work shall be in possession of a written authorization to carry out such hot work issued by the port authority. Such authorization should include details of the specific location of the hot work as well as the safety precautions to be followed.

6.3.2 In addition to the safety precautions required be the port authority, before starting any hot work, the responsible person of the company to carry out the hot work together with the responsible person(s) of the ship and/or port, should add any additional safety precautions required by the ship and/or port.

6.3.3 These should include:

6.3.3.1 the examination, and frequency of re-examination of local areas and adjacent areas, including tests, carried out by accredited testing establishments, to ensure the areas are free, and continue to be free, of flammable and/or explosive atmospheres and, where appropriate, are not deficient in oxygen;

6.3.3.2 the removal of dangerous cargoes and other flammable substances and objects away from the working and adjacent areas. This includes scale, sludge, sediment and other possible flammable material;

6.3.3.3 efficient protection of flammable structural members, e.g. beams, wooden walls, floors, doors, wall and ceiling coverings against accidental ignition; and

6.3.3.4 the sealing of open pipes, pipe lead-throughs, valves, joints, gaps and open parts to prevent the transfer of flames, sparks and hot particles from the working areas to adjacent or other areas.

6.3.4 A duplicate of the hot work authorization and safety precautions should be posted adjacent to the work area as well as at each entrance to the work area. The authorization and safety precautions should be readily visible to, and clearly understood by, all persons engaged in the hot work.

6.3.5 While carrying out hot work it is essential that:

6.3.5.1 checks are carried out to ensure that conditions have not changed; and

6.3.5.2 at least one suitable fire extinguisher, or other suitable fire-extinguishing equipment is readily available for immediate use at the location of the hot work.

6.3.6 During hot work, on completion and for a sufficient time after completion of such work, an effective fire-watch should be maintained in the area of the hot work as well as adjacent areas where a hazard resulting from the transfer of heat may be created.

6.3.7 In addition, Port Facility Occupational Safety Procedures shall be followed.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	48
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

7 Documentation, Control And Record

7.1 Procedures regarding to all necessary documents, information and certification relating to dangerous substances and their procurement and control by the relevant persons

7.1.1 The Operational Division for Hazardous Materials handled by our Port shall develop all records fully and keep the same for submission upon request regarding any hazardous materials

arriving at the port,

shipped from the port,

stored at the port, and

stored at the port on a temporary basis.

The records of hazardous materials are limited to the personnel who need to know the same.

7.2 Procedures of keeping a regular and accurate current list of all hazardous substances in the coastal facility area and other relevant information.

7.3.1 Records of dangerous cargo handled in our port will be kept by the Operations department to include the following information.

- Number,
- PSN name (Proper Shipping Name,
- Class (with lower hazards)
- Packaging Group (Class 3, 4.1, 4.2, 4.3, 5.1, 6.1, 8, 9)
- Marine Pollutant or otherwise
- Receiver,
- Shipper,
- Container / Packaging, number,
- Seal number
- Additional Information (ignition temperature, viscosity, etc.)
- Storage location in the Port Area
- Duration of stay in the Port

7.2.2 This information is recorded on computer or in the file layout so that only authorized personnel can access and presented upon request.

7.2.3 Procedures regarding to appropriate identification of hazardous substances delivered to the facility, correct use of shipping names of dangerous cargo, certification, packaging, labeling and declaration, inspection on loading and transport of dangerous goods in the certified and proper package, container or cargo unit in a safety way and reporting of inspection results.

7.2.4 Coordinately with the Operation, Planning checks the accuracy of the following information through the dangerous cargo documents delivered to the Port and organized by the Shipper;

- Number,
- PSN name (Proper Shipping Name,

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	49
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

- Class (with lower hazards)
- Packaging Group (Class 3, 4.1, 4.2, 4.3, 5.1, 6.1, 8, 9)
- Marine Pollutant or otherwise,
- Containers / Packaging, number,
- Seal number
- Additional Information (ignition temperature, viscosity, etc.)
- Storage location in the Port Area

7.2.5 This information is delivered to the tally clerk, Field Supervisor, Warehouse officer, HSE, and authorized staff through Terminals / Documents and security of the dangerous goods is provided.

7.2.6 In case that information sent from Operation is different from the cargo, Operation will immediately be informed and shipper is instructed to verify the information on Dangerous goods / vehicle /container and correct the incorrect label brands.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	50
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

7.3 Procedures regarding to appropriate identification of hazardous substances delivered to the facility, correct use of shipping names of dangerous cargo, certification, packaging, labeling and declaration, inspection on loading and transport of dangerous goods in the certified and proper package, container or cargo unit in a safety way and reporting of inspection results.

7.3.1 Coordinately with the Operation, Planning checks the accuracy of the following information through the dangerous cargo documents delivered to the Port and organized by the Shipper;

- Number,
- PSN name (Proper Shipping Name,
- Class (with lower hazards)
- Packaging Group (Class 3, 4.1, 4.2, 4.3, 5.1, 6.1, 8, 9)
- Marine Pollutant or otherwise,
- Containers / Packaging, number,
- Seal number
- Additional Information (ignition temperature, viscosity, etc.)
- Storage location in the Port Area

7.3.2 This information is delivered to the tally clerk, Field Supervisor, Warehouse officer, HSE, and authorized staff through Terminals / Documents and security of the dangerous goods is provided.

7.3.3 In case that information sent from Operation is different from the cargo, Operation will immediately be informed and shipper is instructed to verify the information on Dangerous goods / vehicle /container and correct the incorrect label brands.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	51
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

7.4 Procedures related to procurement of the Hazardous materials safety information sheets (SDS).

7.4.1 According to the Laws of our country as of January 1st, 2014, Dangerous Goods Safety Data Sheet (SDS) with the following information must be present with the dangerous goods to be transported through all transport modes (by road, rail, air and marine).

- Number,
- PSN name (Proper Shipping Name,) (required for marine transport)
- Class (with lower hazards)
- Packaging Group (Class 3, 4.1, 4.2, 4.3, 5.1, 6.1, 8, 9)
- Marine Pollutants or otherwise,
- Tunnel Restriction Code (required for road transport.

7.4.2 It is checked that if this document is available with the Dangerous substance for the all Dangerous goods to be accepted in the port.

l imakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	52
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

7.5 **Procedures for records and statistics of dangerous goods.**

7.5.1 A quarterly report containing information on hazardous cargo handled in our Port Facility is submitted to the Port Authority..

7.5.2 Statistical evaluation of records of dangerous goods handled in our port is carried out by our Trade, operation departments.

7.5.3 Monthly inventory and control reports of Dangerous goods stocked in our Port Area is organized by the operation department and submitted to Administration.

7.5.4 Records and reports are archived by department by 5-year periods

7.6 Information on the Quality Management System

Our port fulfills the requirements of ISO 9001 Quality Management System and reviews the system regularly.

ISO 14001 Environmental Management System and ISO 45001 Occupational Health and Safety Management System are managed in an integrated manner, together with the Quality Management System, which forms the basis of the Management Systems.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	53
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

8 EMERGENCY SITUATION, EMERGENCY PREPAREDNESS AND RESPONSE

8.1 Response procedures for hazardous substances that are dangerous for life, property and/or environment and hazardous situations involving hazardous materials

8.1.1 The choice of protective actions for a given situation depends on a number of factors. For some cases, evacuation may be the best option; inothers, sheltering inplace may be the best course. Sometimes, the set woactionS may be used in combination. In any emergency, officials need to quickly give the public instructions. The public will need continuing information and instructions while being evacuated or sheltered in-place.

8.1.2 Proper evaluation of the factors listed below will determine the effectiveness of evacuation or in-place protection (shelter in-place). The importance of these factors can vary with emergency conditions. In specific emergencies, other factors may need to be identified and considered aswell. This list indicates what kind of information may be needed to make the initial decision.

8.1.2.1 The Dangerous Goods

- 8.1.2.1.1 Degree of health hazard
- 8.1.2.1.2 Chemical and physical properties
- 8.1.2.1.3 Amount involved
- 8.1.2.1.4 Containment/control of release
- 8.1.2.1.5 Rate of vapor movement

8.1.2.2 The Population Threatened

- 8.1.2.2.1 Location
- 8.1.2.2.2 Number of people
- 8.1.2.2.3 Time available to evacuate or shelter in-place
- 8.1.2.2.4 Ability to control evacuation or shelter in-place
- 8.1.2.2.5 Building types and availability
- 8.1.2.2.6 Special institutions or populations, e.g., nursing homes, hospitals,

prisons

8.1.2.3 Weather Conditions

- 8.1.2.3.1 Effect on vapor and cloud movement
- 8.1.2.3.2 Potential for change
- 8.1.2.3.3 Effect on evacuation or shelter in-place

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	54	
	DANGEROUS CARGO HANDLING GUIDE					

8.1.3 **Protective Actions**

8.1.3.1 Protective Actions are those steps taken to preserve the health and safety of emergency responders and the public during an incident involving releases of dangerous goods.

8.1.3.2 Isolate Hazard Area and Deny Entry means to keep everybody away from the area if they are not directly involved in emergency response operations. Unprotected emergency responders should not be allowed to enter the isolation zone.

8.1.3.3 This "isolation" task is done first to establish control over the area of operations. This is the first step for any protective actions that may follow.

8.1.4 Evacute

8.1.4.1 Evacuate means to move all people from threatened area to a safer place. To perform an evacuation, there must be enough time for people to be warned, to get ready, and to leave an area. If there is enough time, evacuation is the best protective action.

8.1.4.2 Begin evacuating people near by and those outdoors in direct view of the scene. When additional help arrives, expand the area to be evacuated downwind and crosswind to at least the extent recommended in this guidebook. Even after people move to the distances recommended, they may not be completely safe from harm.

8.1.4.3 They should not be permitted to congregateat such distances. Send evacuees to a definite place, by aspecific route, far enough away so they will not have to be moved again if the wind shifts.

8.1.5 Shelter In-Place

8.1.5.1 Shelter In-Place means people should seek shelter inside a building and remain inside until the danger passes. Sheltering in-place issued when evacuating the public would cause greater risk than staying where they are, or when an evacuation cannot be performed. Direct the people inside to close all doors and windows and to shut off all ventilating, heating and cooling systems.

8.1.5.2 In-place protection (shelter in-place) may not be the best option if

- **8.1.5.2.1** the vapors are flammable;
- 8.1.5.2.2 if it will takealong timefor the gas toclear the area; or
- **8.1.5.2.3** if buildings cannot beclosedtightly.

8.1.5.2.4 Vehicles can offer some protection for ashort period if the windows areclosed and the ventilating systems are shut off. Vehicles are not a seffective as buildings for in-place protection.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	55	
	DANGEROUS CARGO HANDLING GUIDE					

8.1.5.3 It is vital to maintain communications with competent persons in side the building so that they are advised about changing conditions. Persons protected-in-place should be warned to stay far from windows because of the danger from glass and projected metal fragments in a fire and/or explosion.

8.1.5.4 Every dangerous goods incident is different. Each will have special problems and concerns. Action to protect the public must be selected carefully. These pages can help with initial decisions on how to protect the public. Officials must continue to gather information and monitor the situation until the threat is removed.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	56		
	DANGEROUS CARGO HANDLING GUIDE						

8.2 Information on resource, capability and capacity of the coastal facilities regarding to respond to emergencies.

8.2.1 The facility features an approved fire plan. Firefighting teams shall be created for each shift. Demonstrations and exercises, either scheduled or unscheduled, shall be provided for training purposes within the scope of various scenarios at indefinite times. The firefighting equipment stipulated by the approved plan shall be made available fully and maintenance, inspection and test activities shall be conducted for the same.

8.2.2 The facility has an approved action plan against Environmental and Marine Pollution. For each shift, pollution-fighting teams are created. Demonstrations and exercises shall be provided twice a year within the scope of a scheduled scenario, and the reports and records of the same shall be kept. The equipment relating to Environmental and Marine Pollution shall be stored at the facility with counting and inspections in place. Additionally, the facility shall have a protocol for materials stored in the area to ensure support in case of circumstances with inadequate means.

8.2.3 The response teams shall be appointed against the spillage of hazardous materials in line with this guideline and pursuant to IMDG Code.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	57	
	DANGEROUS CARGO HANDLING GUIDE					

8.3 Regulations related to the first aid for accidents involving dangerous substances (first aid procedures, first aid resources and capabilities and so on.).

8.3.1 In case of occurrence of emergency or detecting its symptoms, Emergency Manager (EM) initiate the appropriate measures pursuant to Emergency Management System (EMS) according to the relevant plans.Emergency Management Group (EMG) reviews the decisions regarding to the measures to be taken within scope of the IMDG Code and IMDG Code and put it into effect. Improvements continuously monitored by EMG and taking higher level of measures or help are decided, if needed..

8.3.2 EMG operations will be carried out by Emergency Management Center (EMC) or its equivalent. Emergency management at different levels depending on the severity of emergencies:

Facility / Site Institutions County, EMC City EMC Describes to be menored

Possible to be managed by the central government.

8.3.3 Emergency Management at the facility level will be performed by using safe, fast internal and external communication opportunities with well designed organization, personnel prepared with training and exercises, Emergency Plans including procedures and documentation. The Emergency Management processes will be followed and controlled by basically applying the following measures.

Related Sections
All Personnel and
Ship
All Personnel
Response teams
-
All Personnel
having First Aid
Training
First Aid Personnel
Security Personnel
Press and Public
Relations
Authority

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	58	
	DANGEROUS CARGO HANDLING GUIDE					

8.4 On-site and off site Notifications required to be made in case of emergency

In case of emergencies in the port area, the on-site and off-site emergencies to be notified are given in Annex-11.3 and are as follows.

Emergency situations to be reported within the facility;

- All accidents that occur within the scope of OHS
- Small-scale spills
- Traffic problems within the port
- Operational problems
- Technical failure
- Low medical injuries

Emergency situations to be reported outside the facility:

- Earthquake
- Flood/inundation
- Fire/Explosion
- Sea pollution
- Ship grounding

Emergency notifications include the following information;

a) When the accident occurred,

b) If known, how the accident occurred and its cause,

c) Place where the accident occurred (shore facility and/or ship), position and impact area,

ç) If there is a ship involved in the accident, information (name, flag, IMO number, owner, operator, cargo) and amount, captain's name and similar information),

d) Meteorological conditions,

e) UN number of the dangerous goods, proper transport name (dangerous goods

the legislation specified in the definition will be taken as basis) and the amount,

f) Hazard class of the dangerous substance or sub-hazard section, if any,

g) Packaging group of the dangerous substance, if any,

g) Additional risks of the dangerous substance, such as marine pollutants, if any,

h) Marking and label details of the dangerous substance,

i) The packaging, cargo transport unit and container in which the dangerous substance is carried, if any features and number,

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	59	
	DANGEROUS CARGO HANDLING GUIDE					

- i) Producer, sender, carrier and receiver of the dangerous substance,
- j) The extent of damage/pollution occurring,
- k) Number of injured, dead and missing, if any,

8.5 The procedures for reporting accidents.

8.5.1 Communication

8.5.1.1 Communication channels for the determination of the on-site and off-site communication methods and an effective management of the emergency in case of possible emergency cases in the Port Facility are specified as follows;

- Mobile Phones and the satellite phone, if available
- Computers
- Radio
- Siren
- Messengers olarak belirlenmiştir.

8.5.1.2 Internal communication is primarily provided by the radio and intercom for the emergencies occurred in the port. The communication between the Port and Ship is carried out by radio or VFH marine band radio provided by the Port.

8.5.1.3 Secure communication with the Official authorities, adjacent facilities and relevant authorities are provided as soon as possible in case of any emergency that may occur in the Port.

8.5.2 Reports

8.5.2.1 EMC shall operate a reporting system that correctly notifies Emergencies to the relevant authorities as soon as possible. EMC including the information required to be notified in an emergency case shall create this reports in a proper way.

8.5.2.2 Dangerous cargo accidents must be reported to the Port Authority with the Hazardous Material Incident Notification Form specified in Annex 11-16.

8.6 Coordination, support and cooperation method with authorities.

8.6.1 All accidents related to hazardous materials will primarily be coordinated with Port Authority. Aid units of city / County Fire Department, DEMP and adjacent facilities will provide support and cooperation by informing the Port Authority.

8.6.2 In case of any signs of explosion, fire or emergency noticed at an adjacent facility;

Measures shall be tightened at the facility in the first place,

Teams shall be caused to get prepared for providing with the adjacent facility with assistance

8.6.3 Assistance and support teams shall be assigned for responding to any event in consideration of the urgency of situation and the severity of hazard, if there is no possibility to request help or time.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	60	
	DANGEROUS CARGO HANDLING GUIDE					

8.6.4 Preparations shall be in place for measures such as unloading and reduction of loads and removal of the vessel to anchorage site in case of any interface vessel in consideration of class, quantity and hazard risk of loads available at hazardous cargo site and on site.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	61	
	DANGEROUS CARGO HANDLING GUIDE					

8.7 Emergency evacuation plan for the evacuation of the ship and vessels from the coastal facility in case of emergency

8.7.1 Preparation for Emergency Seperation System

8.7.1.1 All emergencies should be reported to the Port Authority.

8.7.1.2 If the emergency separation of ship is decided, the safe places that the ship can be transferred under controlled conditions must be specified by the Port Authority..

8.7.1.3 In case of an emergency situation that requires emergency separation, the ship's captain and port facilities shall initiate the emergency separation by mutual agreement and inform the situation to the Port Authority as as soon as possible. A representative from Port Authority or Port Master, Terminal Manager / Business Officer, Ship Captain, Guide Captain shall come to a mutual agreement on the time and type of the separation before the immediate action where the severity and time of the emergency allow.

8.7.1.4 The ship's machinery, steering gear and Marine Systems equipment shall be ready for use immediately.

8.7.1.5 All cargo discharge, ballast discharge process must be stopped and shall be prepared for the separation process.

8.7.1.6 Salt water system of the ship must be watered and water mist must be used for strategic departments.

8.7.1.7 If the atmosphere needs vent operation, the engine room staff must be ready, all unnecessary receiver entrance must be closed, all the necessary safety measures relating to the normal operation must be fulfilled and and a warning notice must be published.

8.7.1.8 If the necessary responds are over the terminal resources for all emergencies, local police or fire department must be reported immediately.

8.7.1.9 The decision to depart the ship under control is set out on the safety principle and it should cover the following requirements.

8.7.1.10 -	The adequacy of the Trailers

8.7.1.11 - The ships's ability to depart with its own power

8.7.1.11.1 - The availability of a safe place that a ship can or will be taken in an emergency case.

8.7.1.11.2 - Fire-fighting competence

8.7.1.11.3 - The proximity of other vessels

8.7.1.11.4 - Fire Ropes

8.7.1.12 Fire ropes shall be kept on the top and shoulder of the ships as long as the ship is at Port Facility. The eye of the rope should be wound down to the sea level and the section on the board must be tight with at least five rounds to the bollard. Part of the top board of the rope must be stretched from the bollard. A cord that can carry the rope must be tied right before the eyes of the rope and the eye of the rope must be located in a way that it is three meters above the sea level. The eye of rope must be kept at this level while the ship is at Port Facility.

8.7.2 Realization of Emergency Separation

If all the preparations above examined and deemed appropriate, the ship will be immediately departed.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	62	
	DANGEROUS CARGO HANDLING GUIDE					

8.7.2.1 Emergency separation will be provided by the fulfillment of the following processes in order.

8.7.2.2 A close coordination and cooperation between Terminal, Ship and Port Authorities is required for each phase.

8.7.2.3 Emergency Separation Process is as below.

- Activating an alarm
- Inform about the emergency by VHFphone

- Making the first official assessment of the situation between the ship's captain and officer of Port Facility.

- Suspension of operation
- Implementing Port facility and ship emergency plan measures
- Removal of the flexible hose connection.

- The deterioration of the current situation and availability of the aforementioned emergency separation.

- Making the assessment of the situation between the ship's captain, port facility officer, port authority or port master, guide captain

- The decision to the emergency separation
- Inform the adjacent facilities and other vessels

- The deployment of Trailers around the ship for an emergency separation, complement of the preparation and announcement of the situation

- Completing the preparations for the ship by the captain and indicating that it is ready.

Granting approval for the opening of the release hook by the competent person. **ATTENTION!**

THE IMPLEMENTATION OF EMERGENCY SEPARATION PROCESS MUST BE CONSIDERED AS THE LAST RESORT AND SEPARATION HOOKS MUST NOT BE RELEASED BEFORE TAKING ALL NECESSARY MEASURES AND FULFILLING THE CONDITIONS ABOVE.

8.7.3 Post Emergency Separation

8.7.3.1 –Declaration of the decision on vessel back up and navigation route after the separation process of vessel.

8.7.3.2 –Transition / mooring of the vessel to designated area in company with towboats or its own machine

8.7.3.3 –Port Facility: Determining possible damages or deficiencies through examining the port facility

8.7.3.4 –Consideration of the time when the vessel and port facility become available for freight handling

8.7.3.5 -Sharing problems, if any, occurred during emergency separation

An agreement is reached by and between pilotage and towage organizations and onshore facility authorities regarding any fire, explosion or similar emergencies which are likely to arise during loading/unloading.

Adequate towing boats having satisfactory towing power as furnished with necessary equipment to fight fire in line with weather and marine conditions shall reach the scene as soon as possible in case of emergencies pursuant to the protocol executed with the authorized company to remove the vessel away from the facility and move it to a safe location.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	63	
	DANGEROUS CARGO HANDLING GUIDE					

8.8 Procedures for handling and disposal of the damaged hazardous goods and wastes contaminated with hazardous goods.

8.8.1 Waste Collecting and Handling

8.8.1.1 Consequential waste are collected to waste bins taxonomically and handled to be stored properly. Waste occurred as a result of the maintenance process are handled in that scope.

8.8.1.2 Additional waste classes, if available, are provided to be integrated into the current waste classes.

8.8.2 Waste disposal

8.8.2.1 According to the hazardous or non-hazardous properties, the waste collected are isolated from the facility by selling them or using contracted organizations which are in conformity with legal recycling/disposal methods.

8.8.2.2 Opportunities of all contractors and carriers within the body of waste management in terms of appropriate methods of waste handling and/or disposal are examined.

8.8.2.3 In case of any contracting service received for handling, selling and/or disposal of the waste, those contracting companies are observed whether they fulfill their legal liabilities or perform recycling or disposal without damaging the environment.

8.8.2.4 It is an obligation to keep all the records concerning waste disposal.

8.8.3 Contaminated Packages;

8.8.3.1 These waste are empty barrels. If occurred, should be left to the contaminated package area in the dump site and Environmental Consulting Firm and Environmental Management System Supervisor contact with contracted and licensed company to send those contaminated packages through filling up the National Waste Handling Form within the time specified in the laws and regulation. Relevant documents of National Waste Handling Form and other documents are stored in environment folder.

8.8.3.2 Contaminated Waste; are used gloves, waste cottons and work uniforms. When occurred, should be collected at the waste barrel which is located at the exit of the production-warehouse department and then moved to the waste area. Within the time specified in the laws and regulation, Environmental Consulting Firm and Environmental Management System Supervisor contact with contracted and licensed company to send those contaminated packages through filling up the National Waste Handling Form. Relevant documents of National Waste Handling Form and other documents are stored in environment folder.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	64		
	DANGEROUS CARGO HANDLING GUIDE						

8.9 Emergency drills and their records.

8.9.1 Implementation of Practices;

Emergency organization personnel should get various trainings to get ready for their duties with the purpose of providing against emergencies within the facility. If necessary, such trainings must be organized through specialized agencies. In that scope, relevant personnel have received trainings on IMDG CODE regarding Hazardous cargos and have been certified. Practices, which shall be performed in an effort to examine the efficiency of Emergency Plans and be prepared for facts, have to be planned in a way that they will be performed considering the worst scenario likelihood within the facility.

8.9.2 Practice Scenarios;

Planning practices needs two anticipations one of which is a single incident that the port experience and the other is the worst scenario with the combination of these single incidents. In accordance with the scenarios prepared, practices are ensured to be performed in the fastest and most efficient way possible.

8.9.3 Emergency Practices which will be performed within the facility;

8.9.3.1 Have to be indicated within annual training plans.

8.9.3.2 May be planned as local or general responses,

8.9.3.3 Safety, Spillage, etc. may be combined in practice scenarios,

8.9.3.4 Practices can be performed with or without notices.

8.9.3.5 Practices are based upon different emergency scenarios.

8.9.3.6 A practice may be actually performed as it can be negotiated as a desk work or a seminary,

8.9.3.7 Each practice is prepared with scenarios of different hours, days, seasons and incidents.

8.9.3.8

8.10 Information on fire protection systems.

8.10.1 Emergency and fire equipment is given as follows:

Fire hydrants, Fire extinguishers, fire truck, Fire cabinets and Fire hoses, On-site fire alarm detectors, Electrical and diesel fire pumps

The fire inventory is as in the Emergency Plan.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	65		
	DANGEROUS CARGO HANDLING GUIDE						

8.11 Procedures for approval, inspection, testing, maintenance and availability of the fire protection system.

8.11.1 Fire-Protection Water Tanks and Fire-Protection Water

8.11.1.1 Weekly and annual maintenance is done in order to prevent any disruption of the water outlet in the fire water tanks.

Urgent action is taken and necessary maintenance and cleaning works are carried out in the event of any incident that prevents the water outlet.

8.11.1.2 In case of sudden drawdown on water level, it must be checked for a seep or leakage and repaired if necessary.

8.11.1.3 Following the annual check, if necessary, internal and external cleaning and maintenance should be performed in sealed stores.

8.11.2 Fire-Protection Water Pumps

8.11.2.1 Points to take into consideration regarding operation of pumps and troubleshooting i addition to scheduled maintenance are specified below.

8.11.2.1 Pumps, stuffing boxes, pressure bolts are checked interrelated and it is ensured whether the pump can be turned up manually with ease or not. Water drops from stuffing box during the operation of the pump is typical. In order to prevent such water flow to the ground, the threaded opening under the stuffing box must be connected to the drainage with a tube.

8.11.2.2 Fire-protection water pumps must be operated and recorded at least 1 hour a week.

8.11.2.3 Pump and suction pipe are ensured to be completely full of water. If it is not, water filling plug and bleed valve must be opened and such parts mentioned must b e filled up with water until they overflow and when the water stops at the plug level, the plug must be tightened properly.

8.11.2.4 Pump motor will draw excessive current because of the starting current at the early stages of the operation. As a result of the simultaneous operation of all pumps, cutout switches may be tripped or diesel generators may be broken down seriously because of the heavy current. Therefore, limit relays that regulates the transition -from the star located at the shielded switch which drives the pump motors to triangle- must be arranged according to the number of pumps and the amount of pumps to be operated simultaneously and with respect to different and appropriate time intervals and timely initiation of pumps is provided.

8.11.2.5 After performing aforesaid preliminaries and checks, pumps are operated by pressing the drive switches. During the operation, electric motor voltage and the ampere driven must be checked from time to time. If the ampere driven is high at normal operation, a troubleshooting is needed. There may be a mechanical breakdown or force at the pump or motor. Substandard voltages may be hazardous for motor.

8.11.2.6 Monometers must be checked regularly and one or more pumps must be stopped in case of excess pressure increases.

8.11.2.7 Delivery pipes of pumps must be equipped with valves initially and check valves thereon.
LimakPort	Döküman No	Yayın Tarihi Rev. No Tarihi		Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	66
	DANGEROUS CARGO HANDLING GUIDE				

8.11.2.8 If the check valve of the failed pump on the delivery pipe is blocked by materials such as paper, garbage, pieces, moss, mud and interrupts the proper close of the check valve, a part of the water pumped by the other pumps is pumped to the pool while passing through this failed pumps and suction pipes. This failure blocking the water discharge must be fixed in condition of fire occurrence. If a spinning is detected on some of the couplings of failed pumps during the operation of a part of the pumps, it must be interpreted as a sign for the above mentioned failure.

8.11.2.9 It must be ensured that the pump and the engine are at the right direction during the operation. For that reason, return path must be drawn on the coupling and control must be performed accordingly.

8.11.2.10 The bearings of the pump and engine must not be hotter than hands can resist. If the heat is high, it may be resulted from an internal mechanical forcing or coupling maladjustment. In such situations pump must be stopped and the failure must be corrected immediately.

8.11.2.11 For pumps driven by diesel engine, starting the engine must be carried out in line with the instructions.

8.11.2.12 In condition that a deficiency or malfunction is detected as a result of control, it is fixed by the responsibles.

8.11.3 Sprinkler System

8.11.3.1 The most important point and maintenance to do about sprinkler installation is preventing sprinkler head to be congested. To supply this; sprinkler should be worked according to standards/legislations and should be sure that it is working. Sufficient sprinkler head should be keep in every facility and in case of failure, it should be replaced with new ones, broken ones should be towed by repairing.

8.11.4 Fire Protection Hydrant Installation

8.11.4.1 Entering rain water into fire-protection hydrant hose closets should be prevented; hoses should be without fracture, solid and constricted enough. At least one of the hoses should be maintained as always connected to fire protection valve.

8.11.4.2 Fire-protection valves should be impermeable and working. Broken nozzles, valves and hoses should be replaced immediately and faults should be repaired and towed. Therefore, sufficient hose, nozzle, fire-protection valve, clamp, sleeve and spare materials belong to those should be kept. Waiting the failure is not allowed with any reason at firefighting equipment.

8.11.4.3 While determined failures were fixing after drills, running fireprotection hoses shouldn't be put into closet with water in it. Facilities should supply proper hose suspension to drain the water off in hoses and to be dry and facilities shouldn't replace before ensuring that hose is quite dry. If sea water was ejaculated by hoses, firstly inside of them should be washed by fresh water and then they should be dried at a windy place.

8.11.4.4 All pipes belong to installation of sprinkler and fire-protection hydrants are has to be controlled in general every three months, rusty parts should be painted, decayed parts should be replaced, valves and retched valves should be controlled and failure should be fixed.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	67
	DANGEROUS CARGO HANDLING GUIDE				

8.11.4.5 If any lack or malfunction is determined as a result of all fire-protection hydrants, hoses, and nozzles control it is fixed by related liable.

8.11.5 Portable Extinguishers

8.11.5.1 Sufficient quantity of spare device should always be in facility storages for failure, control and maintenance. Instead of extinguishers those were used for purposes above should be replaced with reserves.

8.11.5.2 All extinguishers are had visual test monthly and inspected. After control, extinguishers' upper surface is marked. During the control, especially extinguishers with dry powder are turned down and slightly hit the base, so powder in pipe is allowed to move. Otherwise, powder in extinguishers stays at same location for a long time can be hardened by subsiding to base. After the result of control; if any lack or malfunction is determined, it is fixed by related liable.

8.11.5.3 Extinguishers are inspected annually in general by firm according to TS ISO 11602-2 Fire Protection: Portable and wheeled extinguisher standard. Extinguishers are tested by related firm in ten years most intervals, chemical powder is inspected at the end of the 4th year.

8.11.6 Protection against freezing.

8.11.6.1 Protection of Generators

8.11.6.1.1 By outside temperature's decreasing under +4C, water may start to freeze. Therefore, radiator's generators with water-cooled motor should be ensured with antifreeze.

8.11.6.2 Protection fire-protection water pumps.

8.11.6.2.1 Fire-protection water pumps and absorption pipes are always full with water. So ambient temperature shouldn't be under +4 C.

8.11.6.3 Protecting of fire-protection distribution pipes.

8.11.6.3.1 Main pipes and branch pipes are had to be protected against the freezing about hydrant sinks. So, lines are protected against freezing by isolation or being floored underground.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	68
	DANGEROUS CARGO HANDLING GUIDE				

8.12 The measures to be taken in case of failure on fire protection systems.

8.12.1 The facility is a system with established alternative competency which backs up firefighting equipment.

8.12.2 The support of adjacent facilities, Fire departments and AFAD (Disaster and Emergency Management Directorate) shall be sought in cases where the facility's own fire fighting equipment is inadequate or out of service.

8.12.3 Other hazardous and combustible materials / vehicles, which are likely to be affected from fire, shall be removed away from the area, if possible.

8.12.4 A necessity may arise to determine under which conditions assistance and support are provided and their scope.

8.12.5 The capabilities of towing boats or marine vehicles featuring marine fire extinguishing system available in the area should be taken into consideration.

8.13 Other risk control equipment.

9 SAFETY AND HEALTH AT WORK MEASURES

9.1 Occupational health and safety measures.

Harbor Structure Management is obligated to take all necessary measures to prevent employees to be affected of these substances, if this is not possible; minimizing it and to protect employees from the danger of these substances when working with chemical substances.

9.1.1 Risk assessment

9.1.1.1 Harbor Structure Management is obligated to do a risk assessment in accordance with 29/12/2012 dated, 28512 numbered Occupational Health and Safety Regulation provisions published at official gazette to determine if there is dangerous chemical substance at Harbor Structure and if there is; determining negative effects in terms of employees' health and safety.

9.1.1.2 Following details are specifically considered at risk assessment to be made at studies with chemical substances:

9.1.1.2.1 Danger and harms of chemical substance in terms of health and safety.

9.1.1.2.2 Turkish material safety verse form (SDS)to be provided from sellers, manufacturers or importers.

9.1.1.2.3 Duration, type and level of contagion.

9.1.1.2.4 Quantity, conditions of usage and frequency of usage of chemical substance.

9.1.1.2.5 Vocational exposition limit values and biological limit values given at annexes of this regulation

9.1.1.2.6 . Effect of preventive measures to be taken or taken.

9.1.1.2.7 If available, results of last health surveillance.

9.1.1.2.8 Each of these substances and their interactions with each other at works that was worked in with more than one chemical substances.

LimakDort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	69
	DANGEROUS CARGO HANDLING GUIDE				

9.1.1.3 Harbor Structure Management obtains extra information from supplier or other sources that is necessary for risk assessment. This information also includes special risk assessments involved in current regulations if available intended for users.

9.1.1.4 A new activity includes dangerous chemical substance is only started after taking all types of measures those were specified by doing risk assessment.

9.1.1.5 Measures to be taken at studying when dangerous chemical substances.

9.1.1.5.1 Risks in terms of employees health and safety when studying with dangerous chemical substances are disabled or minimized with following measures:

9.1.1.5.2 Proper regulation and organization of work are done at Harbor Structure.

9.1.1.5.3 Studies with dangerous chemical substances are made with minimum number of employees.

9.1.1.5.4 Substance quantity and exposition period employees will be exposed is allowed to be at minimum level.

9.1.1.5.5 Chemical substance quantity to be used at Harbor Structure is kept at minimum level.

9.1.1.5.6 Work place building and extensions are always kept clean and neat.

9.1.1.5.7 Proper and sufficient conditions are provided for employees' personnel cleaning.

9.1.1.5.8 Necessary regulations are made to store, transport, use and process dangerous chemical substances, waste and residuals properly at Harbor Structure.

9.1.1.5.9 Safe or less dangerous chemical substance is used instead of dangerous substance in terms of employees' health by using substitution method. If substitution method can't be used because of specification of the work, according to risk assessment result and with order of precedence, following measures are taken and risk is reduced:

9.1.1.5.10 Proper process and engineering control systems are chosen by also considering technological developments at studying with dangerous chemical substances involving maintenance and repair works those can be hazardous in terms of employees' health and safety.

9.1.1.5.11 Block protection measures like installing sufficient ventilation system and proper work organization are taken to prevent risk at its source.

9.1.1.5.12 In case of taken measures for protecting employees collectively against chemical substances' negative effects are not sufficient, personnel protection methods are adopted with these measures.

9.1.1.6 Sufficient control, supervision and inspection is made to allow taken measures to be active and perpetual.

9.1.1.7 Harbor Structure Management provides analysis and measurements of chemical substances regularly those could be hazardous for employees health. If any changing is realized at conditions those can effect Harbor Structure employees' exposition to chemical substances, these measurements are repeated. Measurement results are assessed by considering vocational exposition limit values specified in this Regulation annexes.

9.1.1.8 Harbor Structure Management, also considers specified measurement results. Every situation vocational exposition limit values are crossed, Harbor Structure Management takes protective and preventive measures to fix this as soon as possible.

9.1.1.9 On condition of remaining Regulation Provision about Protecting Employees from Dangers of Explosive Places secret, Harbor Structure Management makes administrative arrangements and takes technical measurements according to following order of precedence in accordance with turnover's specification involving to process,

LimakPort	Döküman No	Yayın Tarihi	n Tarihi Rev. No Revizyon Tarihi		Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	70
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

store and transport chemical substances, to prevent interacting chemical substances' touching each other mutually on the purpose of protecting employees from dangers which originate from chemical substances' physical and chemical feature, by basing results of risk assessment and risk avoidance principles:

9.1.1.9.1 For inflammable and explosive substances to reach dangerous concentration and having dangerous quantity of chemically unstable substances are prevented at Harbor Structure. If this is not possible,

9.1.1.9.2 Having inflammable sources those can cause fire or explosion at Harbor Structure. Conditions those can cause harmful effect of chemically unstable substances and mixtures are disabled. If this is also not possible,

9.1.1.9.3 . Required measures are taken to minimize or prevent employees to be effected by chemically unstable substances' and mixture's harmful effects in case of fire or explosion originate from inflammable or explosive substances.

9.1.1.10 Protective systems those were provided for protecting work equipment and employees, are designed, produced and supplied in accordance with legislation in force in terms of health and safety. Harbor Structure Management provides all equipment and protective systems to be used at explosive places, to be in accordance with provisions of Regulation About Equipment an Protective Systems Used at Probable Explosive Places (94/9/AT) published at 26392 4 repeated numbered and 30/12/2006 dated official gazette

9.1.1.11 Arrangements to reduce effect of explosion pressure are made.

9.1.1.12 Facility, machine and equipment are allowed to be always under control.9.1.1.13 Minimum safety distances are complied with placing storage tanks those have liquid oxygen, liquid nitrogen and liquid argon at work places.

9.1.2 Emergencies

9.1.2.1 Especially following details are considered in case of emergencies originate from dangerous chemical substances at Harbor Structure on condition of keeping details specified in Regulation about Emergencies at Workplaces published 28681 numbered and 18/6/2013 dated Official Gazette as a secret :

9.1.2.1.1 Preventive measures to reduce negative effects of emergencies are taken immediately and employees are informed about the situation. Necessary studies are done to return emergency to normal and only employees assigned at emergencies to do maintenance, repair and compulsory works and teams came to scene from another place are let to get into effected area

9.1.1.1.2 Personal protective equipment and special security equipment is given to the people allowed to enter the affected area and it is being sure that they are using them as long as the emergency situation goes on. People who do not have personal protective equipment and special security equipment are not allowed to enter the affected area.

9.1.2.1.3 Information about the Dangerous chemicals and emergency situation intervention and evacuation procedures are all ready for use. Workers employed for the cases of emergency at the Port Facility and the establishments active in first aid, emergency medical attention, saving and firefighting outside the work place should be provided with these information and procedures easily. These information include;

9.1.2.1.3.1 For the workers employed for the cases of emergency at the Port Facility and the establishments active in first aid, emergency medical attention, saving and firefighting outside the work place to be ready beforehand and so they can practice the

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Yayın Tarihi Rev. No Revizyon Tarihi		Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	71		
	DAN	DANGEROUS CARGO HANDLING GUIDE					

appropriate attention, the danger resulting from the work done, precautions to take and works to be done,

9.1.2.1.3.1 A special danger or information about the works needed to be done that are likely to happen in an emergency situation

9.1.3 Workers' education and informing them

9.1.3.1 Port Facility Management, provided that the provisions mentioned on the Regulation 15/5/2013 dated 28648 numbered Occupational Health and Safety Education Procedures and Principles remain hidden, ensures the workers' and their representative's training and informing. This training and informing especially include the aspects mentioned below;

9.1.3.1.1 Information gained as a result of the risk evaluation.

9.1.3.1.2 Information about the dangerous substances that may occur or taking place at the Port Facility and about the recognition of these substances, health and security risks, occupational diseases, occupational exposure level values and other legal regulations.

9.1.3.1.3 Necessary precautions and things to do so that the worker's do not danger themselves or the other workers.

9.1.3.1.4 Information on the Turkish material safety data sheets supplied from the manufacturer for the dangerous chemical substances.

9.1.3.1.5 Information on labelling/locking the parts, covers, pumping system and suchlike instalment where the dangerous chemical substances are according to the regulations

9.1.3.2 The training and information to the workers and their representatives on the works with the dangerous substances are a training supported by a verbal or written instruction due to the risk degree resulting from the risk evaluation done and its type. These instructions changes according to the changing conditions.

9.2 Information about the personal protective clothes and procedures to use them

Personal Protective Devices of the Response Teams

Level A

Usage area : Situations where the skin, breathing, eyes and etc. need to be protected in a high standard – gas proof

Positive pressured Tube Breathing Apparatus- SCBA

Protective clothing against the chemicals

Gloves which are chemical proof from inside.

Gloves which are chemical proof from outside.

Boots or long boots, chemical proof, with steel heels.

Thermal underwear, long sleeve and cuffed

Hard Cover

Long sleeved

Double sided wireless connection (No spreading sparks)

Level B

The minimum level needed for the entry and exit to the scene, rather for the liquids to be spilled or scattered.

Positive pressured Tube Breathing Apparatus- SCBA

Protective clothing against the chemicals

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	72
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

Gloves which are chemical proof from inside.

Gloves which are chemical proof from outside.

Boots or long boots, chemical proof, with steel heels.

Hard Cover

Double sided wireless connection (No spreading sparks)

Face mask

Level C

Used when the chemicals in environment are known, when the concentration is decided, when it is decided that the skin and eyes will not get harmed. However continuous measure should be done.

- \rightarrow Full mask, air cleaning filter
- \rightarrow Protective clothing against the chemicals
- \rightarrow Gloves which are chemical proof from inside.
- \rightarrow Gloves which are chemical proof from outside.
- \rightarrow Boots or long boots, chemical proof, with steel heels.

 \rightarrow Hard Cover

- \rightarrow Double sided wireless connection (No spreading sparks)
- \rightarrow Face mask

Level D

Work clothes (emergency intervention team). Requires long sleeved and security shoes/boot. Other Personal protection equipment changes due to the condition of the event. If a problem is to occur about the skin, entries to the scene with these kinds of clothes should not be done.

9.3 Closed Room Entry Permit Precautions and Procedures

As long as the relevant area is not free of dangerous vapors and the oxygen in the area is not sufficient, no one enters the closed or covered areas such as the cargo area, the cargo tank, the empty space around this tank, the cargo carrying area, which contains or may contain dangerous vapor or oxygen-consuming loads, and that access to areas is approved by a responsible person who is trained in the use of the relevant equipment and can correctly interpret the results obtained is ensured. The responsible person records the actions to be taken.

If it is necessary to enter an area that cannot be cleared of hazardous vapors within a reasonable period of time for operational purposes, or if the area will not be cleared of hazardous vapors, the entrance to this area is made only by people with an independent respirator or other necessary protective equipment and clothing. The entire operation is carried out under the direct supervision of the responsible person who has independent breathing apparatus, protective equipment and rescue equipment. Respirator, protective equipment and rescue equipment and rescue equipment introduce a source of ignition into the area.

It is ensured that the entrance to the relevant area is made by following the 'Indoor working procedure PR-ISG-001', which is defined in international laws and guides and established by LimakPort.

'Indoor control registration form' prepared by OHS is applied during indoor entry in our facility

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	73
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

Limal	k Port Jerun			КАРА	LI ALAN KO	ONTROL KAYIT FORM	U			Dokü Y	.man Kodu:FR-Ì 'ayın Tarih:01.0 Rev Rev. Tarihi:14.1
Kontrolün \	Yapıldığı Yer				İzleme ve	Ölçme Planı No					
Tarih					İşin Başlar	na Saati					
Kontrolü Ya	apan/Yapanlar				İşin Bitiş S	aati					
					Mevzuat/	Standart					
								Ölcü	m Parame	treleri	
Sıra No	Çalışanlar	Giriş Saati	Çıkış Saati	Kontrol	Yöntemi	Kontrol Saati	O2 (%)	Yanıcı (9	Madde 6)	Sicaklik (0 °C)	Diğer
1											
2											
3											
4											
5											
6											
7											
8											
9											
10											
12											
13											
14											
15											
16											
17											
18											
19											
20											
	Kontrol Ed	len			İlgili	i Alan Sorumlusu			İSG	Uzmanı	

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	74	
	DANGEROUS CARGO HANDLING GUIDE					

10 OTHER POINT

10.1 Validity of the Hazardous Substances Compliance Certificate.

Validity Date of Port Facility Dangerous Goods Compliance Certificate 14/06/2025

10.2 Responsibilities of the Dangerous Goods Safety Consultant

As in section 2.4.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
İskenderun	RH-TMG-001	02.06.2022	3	16.05.2025	75
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

10.3 Matters for carriers of the hazardous substances arriving/leaving coastal facility by land (matters on required documents that must be available in the road vehicle at the entrance/exit of port or coastal facility area, equipment and tools required for this vehicles, speed limits in the port area etc.).

10.3.1 Packaged dangerous cargoes and bulk dangerous cargoes (liquid or solid):10.3.1.1 Name of the consignor (shipper) and date of delivery to the port area, normally not less that 24 hours before arrival;

10.3.1.2 For packaged dangerous cargoes: the Proper Shipping Names of the dangerous goods, the UN number, the class or, when assigned the division of the goods, including for class 1, the compatibility group letter, (if applicable), any subsidiary risk, the number and type of packages, packing group, the flashpoint range (as appropriate), the quantity and additional information as required by chapter 5.4 of the IMDG Code; **10.3.1.3** for bulk dangerous cargoes: the product name and any other information

required by the relevant IMO code; and

10.3.1.4 the name of the ship into which the dangerous cargoes are to be loaded (if applicable), the ship's agent and the port.

10.3.2 Necessary certificates

Hazardous Cargo Declaration, Hazardous Cargo Transport Dispatch, Multi Mode Hazardous Cargo Form, Hazardous Cargo Manifest, Packaging and Container/Vehicle Loading Certificate, Safety Data Sheet, carrying certificate showing exemption for the shipping under ADR/RID/IMDG Code 3.4 and 3.5, SRC 5 certificate appropriate and valid for transport with regard to shipping under ADR, ADR written instruction, Vehicle Conformity Certificate appropriate and valid for carriage, transport document, CSC Certificate for the shipping made with container, the certificate showing eligibility of the tree in case of using heat treated tree with regard to transport or loading safety and cargo transport unit (CTU), cargo safety certificate signifying that container or the cargos in vehicle are secured within the scope of IMDG Code,

As regards the cargos to which fumigation application is made or contain hazardous gas in the cargo transport unit leaving port facility and the cargo transport units arriving port facility, the result of risk evaluation or transport conformity certificate if gas measurement is done,

Without lack of compulsory documents regarding the transport listed above, hazardous cargo that arrives port facility and leaves port facilities cannot be shipped. The cargos not taken under security in appropriate way within the scope of IMDG Code is treated as hazardous cargo too.

10.3.3 Speed Limit in Port Facility

Speed limit in our port facility is 20 km.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	76
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

10.4 Matters for carriers of the hazardous substances arriving/leaving coastal facility by sea (matters on day/night signals to be shown by ships carrying hazardous goods and vessels, cold and hot work procedures in ships and so on.)

10.4.1 Arrival by Sea

10.4.1.1 Packaged hazardous cargos:

10.4.1.1.1 Name and IMO number of ship, agency and estimated time of arrival (ETA), 24 hours at the latest from arrival normally;

10.4.1.1.2 Suitable Dispatch name of hazardous cargos, UN no, class for class 1 or determined part of products, suitability group letter (where applicable), if any, subrisk, parcel number and type, packaging group, interval of flash point (where applicable), amount and the additional information necessitated with IMDG Code chapter 5.4;

10.4.1.1.3 each cargo, dispatch or item in list should be numbered successively for easy reference.

10.4.1.1.4 stacking of hazardous cargo in a way to mark the ones to be unloaded and left in ship;

10.4.1.1.5 the hazardous cargo to be left in ship should be indicated in a manner to refer the numbers in list (see above)

10.4.1.1.6 condition of hazardous cargos in case of possibility of occurence an unappropriate hazard and

10.4.1.1.7 any known defect that will able to affect security of ship or port area.

10.4.1.2 Hazardous bulk cargo (liquid or solid);

10.4.1.2.1 name and IMO number of ship, agency and estimated time of arrival (ETA), 24 hours at the latest from arrival normally;

10.4.1.2.2 a list showing product name of hazardous cargos and other information necessitated with related IMO Code

10.4.1.2.3 A valid International Conformity Certificate for Bulk Transport of Hazardous Chemicals or a valid Conformity Certificate for Transport of Bulk Hazardous Chemical, whicihever is appropriate, International Pollution Prevention Certificate for Liquid Bulk Substances hazardous for Health (NLS Certificate) and/or International Fuel Pollution Prevention Certificate should be made available for cargo;

10.4.1.2.4 Hazardous cargos to be left in ship should be indicated in a way to refer the numbers in list;

10.4.1.2.5 The unitized carries which enter in a solid cargo terminal should also specify qualification of the last three cargos and where applicable, flash points and current situation of tank/cargo holes (i.e. if they are gasless)

In the event of occurrence of any inconvenient danger, situation of hazardous cargos and taking under protection of cargo and transport system, the equipment related to the cargo shipped bulkly and a defect known in instrumentation and

10.4.1.2.6 any known defect that may influence security of port area or ship

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	77	
	DANGEROUS CARGO HANDLING GUIDE					

10.4.1.3.7 The additional information to be presented to port administration before hazardous cargos are brought port area or taken out of port area may be those indicated in ISPS Code Chapter B. The samples of other information necessitated by regulatory voards concerning packaged hazardous cargos are:

- .1 Container number
- .2 shipping license no or reference (if IMDG Code is class 1 or 7)
- .3 name and communication details of receiver or local carrier (if available)

10.4.2 Departure by Sea

10.4.2.1 Packaged hazardous cargos:

10.4.2.1.1 name of ship and IMO number of ship, agency and estimated time of departure (ETD) as necessitated by regulatory boards;

10.4.2.1.2 Suitable Dispatch name of hazardous cargos, UN number, class for class 1 or established part of products, conformity group letter (where applicable), sub-risk if any, parcel number and type, packaging group, flash point interval (where applicable), amount and the additional information necessitated by IMDG Code chapter 5.4;

10.4.2.1.3 stacking place on board of hazardous cargos.

10.4.2.2 hazardous bulk cargos (liquid or solid):

10.4.2.2.1 name of ship and IMO number of ship, agency and estimated time of departure (ETD) as necessitated by regulatory boards;

10.4.2.2.2 a list showing product name of hazardous bulk cargos and other information necessitated by related IMO Code

10.4.2.2.3 A valid International Conformity Certificate for Bulk Transport of Hazardous Chemicals or a valid Conformity Certificate for Transport of Bulk Hazardous Chemical, whichever is appropriate, International Pollution Prevention Certificate for Liquid Bulk Substances hazardous for Health (NLS Certificate) and/or International Fuel Pollution Prevention Certificate should be made available for cargo; **10.4.2.2.4** Stacking on board or place of hazardous cargos.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	78	
	DANGEROUS CARGO HANDLING GUIDE					

10.5 Additional points will be added by the port facility.

10.5.1 Training

10.5.1.1 Management

10.5.2.1 Management should ensure that all shipboard and shore personnel involved in the transport or handling of dangerous cargoes or in the supervision thereof are adequately trained, commensurate with their responsibilities within their organization.

10.5.2.2 Management at all levels should exercise day-to-day responsibility for health and safety. In order to draw up safe operational procedures for the transport and handling of dangerous cargoes, management should carry out an assessment of the risks involved. In certain cases a quantified risk assessment may be necessary.

10.5.1.2 Personnel (cargo interests, port operators and ships)

10.5.1.2.1 Every person engaged in the transport or handling of dangerous cargoes should receive training on the safe transport and handling of dangerous cargoes, commensurate with his responsibilities.

10.5.1.3 Shore-based personnel

Should receive general awareness/familiarization training, function-specific training and safety training

10.5.2 Training content

10.5.2.1 General awareness/familiarization training

10.5.2.1.1 Every person should receive training on the safe transport and handling of dangerous cargoes, commensurate with his duties. The training should be designed to provide familiarity with the general hazards of relevant dangerous cargoes and the legal requirements. Such training should include a description of the types and classes of dangerous cargoes; marking, labelling and placarding, packing, segregation and compatibility requirements; a description of the purpose and content of the transport documents; and a description of available emergency response documents.

10.5.2.2 Function-specific training

10.5.2.2.1 Every person should receive detailed training concerning specific requirements for the

10.5.2.2.2 transport and handling of dangerous cargoes which are applicable to the function that he performs.

10.5.2.3 Safety training

10.5.2.3.1 Each person should receive training commensurate with the risks in the event of a release ofdangerous cargoes and the functions he performs, on:

10.5.2.3.2 Such training should be provided or verified upon employment in a position involving the transport or handling of dangerous cargoes and should be periodically supplemented with retraining, as deemed appropriate by the regulatory authority.

10.5.2.3.3 Records of all safety training undertaken should be kept by the employer and made available to the employee if requested.

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	79	
	DANGEROUS CARGO HANDLING GUIDE					

11 ANNEXES

11.1 General Layout Plan of the Coastal Facility



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	80	
	DANGEROUS CARGO HANDLING GUIDE					

11.2 General Appearance Photographs of the Coastal Facility







LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	81	
	DANGEROUS CARGO HANDLING GUIDE					

11.3 Emergency Contact Points and Contact Information

UNITS T	UNITS TO BE SEARCHED IN THE FACILITY							
POSITION	NAME SURNAME	TELEPHONE	İNTERPHONE					
GENERAL MANAGER	GÜNDÜZ ARISOY							
OPERATIONS DIRECTOR	TEMEL SEZER		4769					
OCCUPATIONAL HEALTH AND SAFETY MANAGER	CEREN ÇOLAK		4844					
SECURITY AND ADMINISTRATIVE OPERATIONS RESPONSIBLE	SERDAR DİNÇER	0000 000 40 00	4845					
TECHNICAL MAINTENANCE DIRECTOR	UFUK ŞAFAK	0326 626 16 00	4803					
DOCTOR	MEHMET ÖZONUR		4854					
ENVIRONMENT AND QUALITY MANAGER	HAKAN GÜNGÖRDÜ		4532					
FIRE SAFETY CHIEF	FETULLAH TOKGÖZ		4659					

UNITS TO BE SEARCHED OUTSIDE THE FACILITY						
UNIT	PRIORITY	TELEPHONE				
İSKENDERUN PORT AUTHORITY	1	0-326-614 11 92				
ISKENDERUN MUNICIPALITY FIRE DEPARTMENT	1	112				
COAST GUEST ISKENDERUN GROUP COMMAND	1	0 326 614 23 11				
FIRST AID	1	112				
STATE HOSPITAL	1	0 326 615 37 50				
PRIVATE İSKENDERUN GELİŞİM HOSPITAL	2	0326 618 66 66				
PORT MANAGEMENT DIRECTORATE	2	0 326 614 00 47				
ISKENDERUN CUSTOMS CHIEF DIRECTORATE	2	0 326 613 81 82				
POLICE HELP	2	155				
GENDARME	2	156				
HATAY PROVINCIAL AND DISASTER EMERGENCY DIRECTORATE	2	0 326 216 10 67				

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	82	
	DANGEROUS CARGO HANDLING GUIDE					

11.4 General Layout Plan of Areas Where Dangerous Cargoes Are Handled



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	83	
	DANGEROUS CARGO HANDLING GUIDE					

11.5 Fire Plan of Areas Where Dangerous Cargoes Are Handled



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	84	
	DANGEROUS CARGO HANDLING GUIDE					

11.6 General Fire Plan of the Facility



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	85	
	DANGEROUS CARGO HANDLING GUIDE					

11.7 Emergency Plan Available.

Emergency Assembly Places Plan 11.8



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001	02.06.2022	3	16.05.2025	86	
	DANGEROUS CARGO HANDLING GUIDE					

11.9 Emergency Management Scheme



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	16.05.2025	87		
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

11.10 Hazardous Materials Handbook



LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001 02.06.2022 3 16.05.2025					
	DAN	GEROUS CARG	O HANDLI	NG GUIDE		

11.11 Leakage Areas and Equipment, Entry/Exit Drawings for CTU and Packages

It is included in the layout plan.

11.12 Inventory of Port Service Vessels

SHIP'S PARTICULARS	
Ship's Name	M/TUG LIMAK 1 - M/TUG DP WORLD YARIMCA
Call Sign	TCA3916 - TCA3961
Nationality	TURKISH
Port Of Registry	ISTANBUL
Register No	TUGS 2458 - TUGS 2467
IMO Number	9773894 -9773909
IMO Number (MMSI)	271044389 -271044417
GMDSS Sea Area	A3
Owners	LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT
Alloed Voyage Range	UNRESTRICTED NAVIGATION - OFFSHORE TUG
Gross Tonnage	365
Net Tonnage	110
Lenght Overall	25,30 M.
Beam	12,00 M.
Depth	4,6 M.
Draft (max)	5,05 M.
Maximum Heigth from	18.00 M
Keell	16,90 MI.
	MAIN & AUXILARY ENGINES
Туре	FFS
Capacity	1200 m3
Foam Capacity	4,9 m3
Water Monitor	2 * FFS
	TOWING CAPACITY & EQUIPMENTS
Maximum Static Bollars	Dull (Aft Mindlass) E0 Tons
Maximum Static Dollars	Full (Art Windlass) 59 Tons
SHIP'S PARTICULARS	Pull (Art Windlass) 39 Tons
SHIP'S PARTICULARS Ship's Name	_M/TUG DIKOVASI IX
SHIP'S PARTICULARS Ship's Name Call Sign	M/TUG DIKOVASI IX TC9342
SHIP'S PARTICULARS Ship's Name Call Sign Nationality	M/TUG DIKOVASI IX TC9342 TURKISH
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL
Ship's PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20
Ship's PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI)	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356
Ship's PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG
Ship's PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M.
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M.
Ship's PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M.
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max)	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M.
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M.
Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M.
Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M. MAIN & AUXILARY ENGINES
Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M.
SHIP'S PARTICULARS Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell Type Capacity	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M. MAIN & AUXILARY ENGINES FFS 0,853 m3
Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell Type Capacity Foam Capacity	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M. MAIN & AUXILARY ENGINES FFS 0,853 m3 4,9 m3
Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell Type Capacity Foam Capacity Water Monitor	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M. MAIN & AUXILARY ENGINES FFS 0,853 m3 4,9 m3 1 X 200 m3/H Foam dispersants, Remote Fog/Jet Nozzle
Ship's Name Call Sign Nationality Port Of Registry Register No IMO Number IMO Number (MMSI) GMDSS Sea Area Owners Alloed Voyage Range Gross Tonnage Lenght Overall Beam Depth Draft (max) Maximum Heigth from Keell Type Capacity Foam Capacity Water Monitor	M/TUG DIKOVASI IX TC9342 TURKISH ISTANBUL TUGS 20 9208655 271010356 A1 LIMAK ISKENDERUN INTERNATIONAL PORT MANAGEMENT UNRESTRICTED NAVIGATION - OFFSHORE TUG 73,77 M. 18,28 M. 6,7 M. 2,48 M 5,05 M. 10,0 M. MAIN & AUXILARY ENGINES FFS 0,853 m3 4,9 m3 1 X 200 m3/H Foam dispersants, Remote Fog/Jet Nozzle TOWING CAPACITY & EQUIPMENTS

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001 02.06.2022 3 16.05.2025					
	DANGEROUS CARGO HANDLING GUIDE					

11.13 Sea coordinates of Port Authority administrative borders, anchorage areas and pilot disembarkation/embarkation points

The port administrative area of Iskenderun Port Authority is the sea and coastal area located to the east of the line formed by the following coordinates and the line drawn from coordinate (a) to the true south (180°) direction, and bordered by the Turkish Territorial Waters adjacent to this area.

) 36° 25' 15" N – 035° 35' 57" E

b) 36° 49' 48" N – 036° 10' 00"E (Deliçay)

B) Anchorage areas

a) Southern anchorage area: The anchorage area for ships not carrying hazardous materials and military ships is the sea area formed by the following coordinates.

1) 36° 36' 30" N – 036° 08' 30" E 2) 36° 36' 30" N – 036° 07' 00" E 3) 36° 38' 00" N – 036° 07' 00" E 4) 36° 38' 00" N – 036° 08' 30" E

b) Dangerous cargo ships anchorage area: The anchorage area for ships carrying dangerous goods, nuclear-powered military ships, ships to be quarantined, and ships to perform degassing is the sea area formed by the following coordinates.

- 1) 36° 37' 21" N 036° 10' 30" E 2) 36° 37' 21" N – 036° 09' 00" E
- 3) 36° 38' 00" N- 036° 09' 00" E
- 4) 36° 38' 00" N 036° 10' 30" E

c) Eastern anchorage area: The anchorage area for ships not carrying hazardous materials and military ships is the sea area formed by the following coordinates.

- 1) 36° 40' 00" N 036° 10' 30" E
- 2) 36° 40' 00" N 036° 09' 00" E
- 3) 36° 42' 00" N 036° 08' 00" E
- 4) 36° 42' 00" N 036° 09' 30" E

ç) Northern anchorage area: The anchorage area for ships not carrying dangerous goods and military ships is the sea area formed by the following coordinates.

1) 36° 43' 30" N – 036° 09' 00" E

- 2) 36° 43' 30" N- 036° 07' 30" E
- 3) 36° 46' 00" N 036° 07' 30" E
- 4) 36° 46' 00" N 036° 09' 00" E

C) Pilot pick-up and drop-off locations

- 1) 36° 36' 48" N 036° 10' 42" E (South)
- 2) 36° 40' 42" N 036° 10' 30" E (East)
- 3) 36° 44' 00" N 036° 09' 30" E (North)

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001	02.06.2022	3	16.05.2025	90
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

11.14 Emergency Response Equipment Against Marine Pollution in the Port Facility

As in the Approved Marine Pollution Emergency Response Plan

11.15 Personal protective equipment (PPE) usage map

langa Gelaja													×	×							
laynukp terluku													×	*							
lan kanada Kalada													×	×							
timid fener	×							×	×		×	×	×	*		×					
iş tulumu	×				X								X	X	X			X			×
Tulum (Kimyaala Dayariki)																		×			
cueldk												X									
suk tien	×											X						×			
Yla Sperlý (sperita m)										X	X	X		X							
Kimyanin day. Cooldk (geogle)																					
function coologie													X	X							
Tee Otelojo (Yume)	×	×	×	X	×	×	Х	X	×		×	X	X	X	X	X		×	X		×
Ter Obeloĝio (pellor)	×	×	×	X	×	×	X	X	x	X	x	X	X	X	X	X	X	x	X	×	×
Ter Markov (Akr karbonlu 27)																					×
Ter Markeri (1771)	×	×	×		×		X	X	×				X	x			×	×	×		
Tem kepi Alci Given													X	×				×			
Menfiela Neon iş előveni										×	×	x				X	×				
Kuynukp olávoni													X	×							
No-l dáce	×	×		X	×			X	×				X	X	X	X		×	×	×	×
Mentuj ekineni								X	X				X	X	X			X		×	
Yukack Gorlim Elővani										X	×	X									
nefektfi velek	×	×	X	X	×	×	X	X	X	X	X	X	X	X	X	X	X	X	X	×	×
¥			×	×	×	×	X	×	×	×	×	X	X	×	X	X		×	×	~	×
i Ayrikinba (móstadk)	×									×	×	x									
i Ayrikaba (romal)	×	×	×	×	×	×	X	X	×				X	×	X	X	×	×	×	×	×
i diini	×	×	×	X	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×	×
Fasilyet/KKD	Puentörlük	Kaldırma Ekipmanı Kullanma	iş Kontrolü	Konteyner iç Dolum/Boşaltım (Demir, Pamuk vb.)	Konteyner iç Dolum/Boşaltım (Maden vb.)	Konteyner Yükleme, Boşaltma, İstifleme	Dökme Yük Yükleme ve Boşaltma	Proje Kargo Yükleme ve Boşaltma	Genel Kargo Yükleme ve Boşaltma	Elektrik Pano Bakımı	Trafo Bakimi	Jeneratör Bakımı	iş Mekinesi Bekımı	Makine, Ekipman vd. Parça Bakımları	Kablo Çekme	Kamera Montaji ve Bakımı	Bilgisayar Bakım ve Temizliği	Gemiden Atık Alımı	Çevre Temizliği	Gemilere Su Verme	Canlı Hayvan Tahliye,Yükleme

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001 02.06.2022 3 16.05.2025				
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

11.16 Hazardous Material Incident Notification Form

Issue number- Date						
Company / Institution						
Sender		ONTACT IFORMATION				
as required						
PORT FACİLİTY						
"DANGEROUS CARG	O NOTIFICATION"					
DATE:						
1. When the accide	nt occurred,					
2. If the accident is	known, how it occurred and the	reason,				
3. The place where	the accident occurred (Port Facil	lity and/or ship), its posi	tion and are			
of influence, ç) Info	rmation (name, flag, IMO number	er, owner, operator, carg	go, if any) of			
th ship involved in	the accident.					
and amount, captai	n's name and similar information	n),				
4. Meteorological conditions,						

LimakPort Iskenderun	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No	
	RH-TMG-001 02.06.2022 3 16.05.2025					
	DAN	GEROUS CARG	O HANDLI	NG GUIDE		

11.17 Control Results Notification Form for Hazardous Cargo Transport Units (CTUs)

Yıl / Dönem /	Sayı	Yüzdelik
Kontrol edilen paketler:		
Kusurlu paketler:	· *	
. toplam		
. yurt içinde doldurulmuş		
. yurt dışında doldurulmuş		
Kusurlar:		
Dokümantasyon:		
. Tehlikeli Yük Deklarasyonu		
. Konteyner/Araç Paketleme Sertifikası		
Plakalama ve markalama		
Konteyner Güvenlik Sözleşmesi onay levhası		
Ciddi yapısal kusurlar		
Kara tankerleri bağlama eklentileri		
Taşınabilir tank veya kara tankerleri (uygunsuz veya hasarlı)		
Etiketleme (paketler için)		
Paketleme (uygunsuz veya hasarlı)		
Yükün segregasyonu		
Paketin içinin istiflenmesi / bağlanması		

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No
	RH-TMG-001 02.06.2022 3 16.05.2025				
	DAN	GEROUS CARG	O HANDLI	NG GUIDE	

12 ABBREVIATIONS

VHF, Marine Band Radio
CTU, Cargo Transport Unit
IMDG, International Hazardous Materials Guide
IMO, International Maritime Organization
ILO, International Labor Organization
UN, United Nations
PEAR is Harmful to People, Environment, Property and Reputation
UATF, National Waste Transportation Form
AFAD, Disaster and Emergency Management Presidency
SDS, Material Safety Data Sheet

13 PRESENTATION

This Guide applies to the entry and presence of dangerous goods in port areas, both on board and ashore. These are intended to be made applicable to all ships visiting a port, regardless of their flag. It should not be applied to ships' stores and equipment, or to troop transport ships and warships.

2.1 The purpose of this section is to help individuals and institutions preparing national legal requirements to ensure that these requirements are made as effective as possible by specifying all possible situations of dangerous cargoes in cargo areas, but without creating validity for exceptional cases.

It is important to carefully examine and use definitions to avoid misunderstanding.

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No				
	RH-TMG-001 02.06.2022 3 16.05.2025 9								
	DAN	GEROUS CARG	O HANDLI	NG GUIDE					

14 DEFINITIONS

Interface means a dock, breakwater, breakwater, wharf, pier, marine terminal or similar structure (floating or not) to which a ship may be moored. This includes any facility or property other than a ship used directly or indirectly in the loading or unloading of dangerous cargo.

Port Facility means any person or entity that controls a port operation on a daily basis.

Bulk means cargoes intended to be carried without partitions for storage in a tank permanently fixed on or within the Ship or in a cargo area that is a structural part of a Ship.

Cargo companies means a shipper (shipper), carrier, forwarder, groupage agent, packaging center or any person, company or entity involved in any of the following activities: identifying, containing, packing, packing, securing dangerous cargoes, Receiving cargo at the port, transporting it by sea and having control over the cargo at all times regarding its labeling, plate-making or documentation.

Certificate of Conformity means a document issued by or on behalf of the Administration in accordance with the relevant laws for the ship's structure and equipment, certifying that the ship's structure and equipment are suitable for the dangerous cargo to be carried on the ship.

Dangerous cargo means any of the following cargo, whether or not packaged, bulk packaged or transported in bulk, within the scope of the following documents:

Oils covered by MARPOL 73/78 Annex I;

- Gases covered by the Laws for the structure and equipment of ships carrying Liquefied Gases in bulk;

- Toxic liquid substances/chemicals, including wastes, covered by MARPOL 73/78 ANNEX II and the laws for the structure and equipment of ships carrying Hazardous Chemicals in Bulk;

- Safety practices for solid cargoes in bulk (BC Code) include solid materials in bulk containing chemical hazards and solid hazardous materials in bulk (MHBs), including wastes covered by group B annexes in the law;

- Harmful substances in packaged form (covered by MARPOL 73/78 Annex III); And

- Dangerous substances, materials or substances (covered by the IMDG Code).

The term dangerous cargo also includes any uncleaned packaging that has previously carried dangerous cargo, unless it has been filled with a substance that is not classified as dangerous, or has been cleared of gases to neutralize any hazards and the residues of dangerous cargo have not been adequately cleaned (tank-container containment, bulk compartment intermediate containers). (IBCs), bulk packagings, portable tanks or tank vehicles).

Certificate of Conformity means a document issued by or on behalf of the Administration to a ship carrying dangerous goods in bulk solid form or packaged form

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	95		
	DANGEROUS CARGO HANDLING GUIDE						

under SOLAS regulation II-2/19.4, which constitutes evidence that the structure and equipment comply with the requirements of the regulation.

Flexible pipe means flexible hose and end connections containing vehicles with sealed ends used for the transfer of dangerous cargo.

Handling, including intermediate holding operations such as temporary storage of dangerous cargoes in the port area during their transportation from the point of origin to the destination route, in order to change the means and methods of transportation and movement within the port, which forms part of the transportation supply chain for cargoes, and from a ship, railway wagon, vehicle, freight It includes loading or unloading operations from a container or other means of transport, intermediate transport between ships or other means of transport, or transfer within a ship or in a warehouse or terminal area. This term has been expanded to include many operations related to dangerous cargo in the port area.

Hot work means open fire and flame, electrical tools or hot riveting, grinding, welding, burning, cutting, welding or other repair work involving heat or causing sparks that may become hazardous due to the presence of or proximity to hazardous loads.

Captain means the person in command of a ship. Pilot is not included.

Packaging means the packing, loading and filling of dangerous cargoes to receivers, intermediate containers for bulk transportation (IBCs), freight containers, tank containers, portable tanks, railway wagons, bulk containers, vehicles, ship-borne barges or other cargo transportation units.

Pipeline means all pipes, connections, valves and other auxiliary facilities, apparatus and equipment in a port related to or used for the loading of dangerous cargoes, but excluding the ends of parts of the pipes, apparatus or equipment of the ship to which flexible pipes are connected. It will not include the equipment part, flexible pipe, loading arm.

Port area means the land and sea area determined by legislation.

Note: Some port areas may overlap and legal requirements must be taken into account. When creating the definition of the port area in legal regulations, care must be taken to ensure that the law applies to all facilities that may be included.

Port Authority means any person or institution authorized to exercise effective control in the port area.

Authority/Authorities means the national, regional or local authority that has authority to enforce legal requirements and is authorized to enforce legal requirements in relation to a port area.

Responsible Person means a person appointed by a ship's master or a shoreside employer who is certified or otherwise recognized, where appropriate, by the

LimakPort	Döküman No	Yayın Tarihi	Rev. No	Revizyon Tarihi	Sayfa No		
	RH-TMG-001	02.06.2022	3	16.05.2025	96		
	DANGEROUS CARGO HANDLING GUIDE						

Regulatory Authority, who has sufficient knowledge and experience for that purpose and who has the authority to make all decisions in relation to a specific task.

Ship means any seaworthy or non-seaworthy vessel, including those used in inland waters, used for the transportation of dangerous cargo.

Responsible person means a person who has current knowledge, experience and competence to perform a specific task.

Stowage refers to the positioning of packages, intermediate bulk containers (IBCs), freight containers, tank containers, portable tanks, bulk containers, vehicles, ship-borne barges, other cargo transport units, and bulk cargo on the deck, holds, sheds, or other areas of the ship. is coming.

Shipping means movement within port areas by one or more means of transport.

Unstable substance means a substance that, due to its chemical structure, tends to polymerize or otherwise give dangerous reactions under certain temperature conditions or when in contact with a catalyst. Reducing this tendency can be achieved through special shipping conditions or by using sufficient amounts of chemical inhibitors or stabilizers in the product.